

Barnwell Waste Management Facility Site Disposal Criteria Chem-Nuclear Systems Barnwell Office

Revision 24

Authored By:

Billy L. Carver
Billy L. Carver, Technical Services
Coordinator

10/31/13
Date

Reviewed By:

Michael Benjamin
Michael Benjamin, Disposal Operations
General Manager

10-31-13
Date

Approved By:

Joseph J. Still
Joseph J. Still, Licensing Manager/RSO

12-4-13
Date

- ☒ Non-Proprietary
☐ Proprietary
☐ Restricted Information
☐ Safeguards Information
☐ Sensitive Security Information

- ☐ New
☐ Title Change
☒ Revision
☐ Rewrite
☐ Cancellation

Effective
Date

12-12-13

Table of Contents

Section	Page
1. PURPOSE AND SCOPE.....	5
1.1 Purpose.....	5
1.2 Scope.....	5
2. REFERENCES	5
3. GENERAL	6
3.1 Abbreviations	6
3.2 CNS Telephone Numbers	6
3.3 Holidays	6
3.4 Pre-Shipment Requirements.....	6
3.5 Shipment Prior Notification	9
3.6 Shipment Documentation.....	9
3.7 Off-Loading Schedule.....	10
3.8 Driver Check-In Procedure	10
3.9 Delays.....	11
3.10 Retrievability of Disposed Material.....	11
3.11 Equipment Storage.....	11
4. WASTE SCHEDULING	11
5. PRIOR NOTIFICATION PLAN (PNP).....	12
5.1 General	12
5.2 Instructions	12
5.3 PNP Notifications	13
6. WASTE MANIFEST FORMS	13
6.1 General	13
6.2 Instructions	14
6.3 Special Considerations.....	14
7. VOLUME AND WEIGHT MEASUREMENT CRITERIA	14
8. WASTE CLASSIFICATION AND PACKAGING.....	15
9. VAN SHIPMENTS	17
9.1 Drums.....	17
9.2 Packages Weighing Less Than 8,000 Pounds.....	18
9.3 Packages Weighing More Than 8,000 Pounds	18
9.4 Mixed Shipments (Drums, Boxes, Liners, etc., Containing Class A, B, & C Waste).....	19
9.5 Less Than Full Load Shipment	19

10.	FLATBED TRAILER SHIPMENTS.....	19
11.	CASK SHIPMENTS	20
12.	CONTAMINATION LIMITS OF PACKAGE/VEHICLE	21
12.1	General	21
12.2	Floor Covering.....	22
12.3	Decontamination Prior to Release	22
12.4	Contamination Release Limits for Vehicles Exiting the Barnwell Site	22
13.	SPECIAL CATEGORIES	24
13.1	Dry Active Waste	24
13.2	Biological Material	24
13.3	Gaseous Waste.....	26
13.4	Sealed Sources or Special Form Radioactive Materials.....	26
13.5	Liquid Radioactive Waste	27
13.6	Wastes Containing Free Standing Liquids.....	28
13.7	Scintillation Products and Containers.....	28
13.8	Oil.....	29
13.9	Pyrophoric Materials or Flammable Solids	29
13.10	Special Nuclear Material (SNM).....	30
13.11	Hazardous Chemicals	30
13.12	Transuranics (Elements with Atomic Numbers greater than 92.....	31
13.13	Uranium Oxide	32
13.14	Unusual Hazards.....	32
13.15	High Integrity Containers.....	32
13.16	Filter Media/Filters/Resins	33
13.17	Slit Trench Shipments.....	33
13.18	Chelating Agents	34
13.19	Lead.....	34
13.20	Mixed Waste.....	34
13.21	Polychlorinated Biphenyls (PCB's)	35
13.22	Asbestos	36
13.23	Radium Wastes	36
14.	CLASS A UNSTABLE PROCESSED WASTE	36
15.	CLASS C WASTE SHIPMENTS.....	37
16.	IRRADIATED HARDWARE.....	38
17.	LARGE COMPONENTS.....	39
18.	LARGE COMPONENTS DISPOSED WITHOUT VAULTS.....	40

19.	SHIPMENTS NOT AUTHORIZED BY CNS RADIOACTIVE MATERIAL LICENSES	41
20.	SHIPMENTS VIOLATING REGULATIONS OR CRITERIA	41
21.	MULTIPLE GENERATOR SHIPMENTS.....	42
22.	RADIOACTIVE MATERIAL QUANTITIES OF CONCERN (RAMQC) SHIPMENT	43
23.	NATIONALLY TRACKED SOURCES.....	43
24.	ATTACHMENTS.....	44
24.1	Abbreviations.....	45
24.2	CNS Telephone Numbers	46
24.3	Completing Barnwell Waste Management LLRW Manifest Forms	47
24.4	Documentation for Class C Waste Shipment Acceptance at Barnwell Site	59
24.5	Class C Waste Classification Record (Example).....	61
24.6	Barnwell Uniform Low-Level Radioactive Waste Manifest Forms - Example	63
24.7	Displacement of Steel Drums & Standard B-25 Boxes – Drum Volumes	66
24.8	Example Request Approval for Sealed Source/Special Form	67
24.9	Lead Shielding Request - Example.....	68
24.10	Typical Waste Package Data Summary - Example	69
24.11	Irradiated Hardware Liner Inventory Log - Example.....	70

1. PURPOSE AND SCOPE

1.1 Purpose

Chem-Nuclear Systems, LLC (CNS), as a subsidiary of EnergySolutions, accepts low-level radioactive waste (radwaste) material for disposal at the Barnwell Waste Management Facility (Barnwell Disposal Facility) based upon compliance with the requirements and references described in this document, "Barnwell Waste Management Facility Site Disposal Criteria" (Site Criteria). This document outlines the responsibilities of both the customer and CNS and describes what constitutes an acceptable shipment for disposal at the Barnwell Disposal Facility (BDF).

Any deviations from the requirements of the Site Criteria must be approved by the Disposal Operations General Manager, Licensing, or designee to avoid refusal or additional surcharges.

1.2 Scope

This document applies to any individual shipping radioactive waste for disposal to the BDF and to CNS personnel involved with shipping and receiving radioactive material waste shipments for disposal at Barnwell. A copy of the Site Criteria should be retained by the customer's employees responsible for the packaging and shipping of radioactive waste to the BDF.

Any questions regarding the Site Criteria, CNS Licenses, Prior Notification Plan should be directed to the Barnwell Licensing Department (Telephone: 803-541-5011 or 541-5013) unless otherwise specified.

2. REFERENCES

All customers shipping radioactive waste to the BDF for disposal shall comply with the following applicable documents:

- 2.1 CNS's South Carolina Department of Health and Environmental Control (SC DHEC) Radioactive Materials License, No. 097
- 2.2 U.S. Department of Transportation (DOT), Code of Federal Regulations, Title 49
- 2.3 U.S. NRC, Code of Federal Regulations, Title 10
- 2.4 SC DHEC Regulation 61-83, Transportation of Radioactive Waste Into or Within South Carolina
- 2.5 U.S. NRC I.E. Information Notice No. 83-10

- 2.6 U. S. NRC Branch Technical Position on Concentration Averaging and Encapsulation, Dated 1/17/95
- 2.7 SC DHEC Regulation 61-63, Radioactive Materials (Title A)
- 2.8 Additional Security Measurements (ASM) on the Transportation of Radioactive Material Quantities of Concerns issued by the U.S. NRC (EA-05-007, July 19, 2005), and associated NRC updates.
- 2.9 Federal Motor Carrier Safety Regulation, Part 393, Subpart I- Protection Against Shifting and Falling Cargo.
- 3. **GENERAL**
 - 3.1 **Abbreviations**

Abbreviations used in this document are defined in Attachment 24.1.
 - 3.2 **CNS Telephone Numbers**

The telephone numbers of CNS offices are listed in Attachment 24.2.
 - 3.3 **Holidays**

CNS normally observes the following holidays and the BDF will be closed for business on the indicated dates or as specifically noted in separate correspondence:

 - New Year's Day
 - President's Day
 - Memorial Day
 - Independence Day
 - Labor Day
 - Thanksgiving Day and the day after
 - Christmas Day and the day before/or after (contact CNS for schedule)
 - 3.4 **Pre-Shipment Requirements**

The BDF accepts waste by public highway only. The following requirements shall be met before shipping any radioactive waste to the BDF:

 - 3.4.1 Shipments containing wastes with activities totaling 40,000 curies or more must have prior to shipment approval from the Barnwell Licensing Department. The allowable unburied activity level in accordance with Reference 2.1 is 50,000 Curies.

- 3.4.2 Before the receipt of any waste, a contract, in form and substance acceptable to CNS, certifying compliance with the Site Criteria, Reference 2.1, and any subsequent changes, should be in the possession of CNS.
- 3.4.3 For Barnwell disposal contracts and Barnwell disposal pricing information contact the EnergySolutions (ES) Public Affair Department at (803) 758-1825.
- 3.4.4 For pre-paid shipments advance copies of all shipping documents must be on-hand with CNS Billing Department prior to waste receipt.
- 3.4.5 Unless prior agreement has been made between CNS and the customer, "collect" freight shipments shall not be accepted at the BDF. Any demurrage charges shall be paid by the customer.
- 3.4.6 All waste generators, waste collectors, and waste processors, unless otherwise exempted by the State of South Carolina, shall have a valid S.C. Radioactive Waste Transport Permit (See Reference 2.4).
 - 3.4.6.1 Before any shipper/generator, waste collector, or waste processor transports or causes to be transported radioactive waste into the State of South Carolina, they shall purchase an annual Radioactive Waste Transport Permit, (RWTP), from South Carolina Department of Health and Environmental Control, (SC DHEC).
 - 3.4.6.2 Shippers/generators, waste collectors, and waste processors shall ensure that the RWTP is current and valid.
 - 3.4.6.3 For each restricted RWTP, the Broker/Shipper shall ensure that they are **listed** as an authorized Broker of the RWTP.
 - 3.4.6.4 All applications for RWTP's should be completed, signed, and received by SC DHEC 30 days before shipping date.
 - 3.4.6.5 Permit Fees will be assessed by SC DHEC based on the following classifications:
 - 3.4.6.5.1 Class X - More than an annual total of 75 cubic feet or more than 100 curies of radioactive waste for disposal, storage, or waste processing within the State.
 - 3.4.6.5.2 Class Y - An annual total of no more than 75 cubic feet of radioactive waste for disposal, storage, or waste processing within the State.

Note: Y permits may be restricted to specific shippers or carriers. Refer to RWTP.

3.4.6.5.3 Class Z - Any shipment of radioactive waste which is not consigned for disposal, storage, or waste processing within the State, but is transported into or within the State.

Reference 2.4 and permit applications may be obtained from the following office:

S.C. Department of Health and
Environmental Control
Infectious and Radioactive Waste
Management Section
Division of Waste Management
Bureau of Land and Waste Management
2600 Bull Street
Columbia, S.C. 29201

Telephone: 803-898-0442 or 0239
Fax Number: 803-898-0391

3.4.7 All waste shippers shall obtain a Shipment Identification (ID) Number from the CNS Barnwell Licensing Department prior to shipping.

3.4.8 The Shipment ID Number shall be placed on the waste manifest to provide verification to carriers and others involved in radioactive waste transport and the BDF receiving personnel that the radioactive waste shipment has been authorized for receipt.

3.4.9 Radioactive waste shipments that arrive at the BDF without a Shipment ID Number shall NOT be accepted.

3.4.10 All shipments shall meet the requirements of Reference 2.1.

Note: Individual waste containers may be inspected to determine content and/or physical form.

3.4.11 Class C waste shipments must comply with Section 15.

3.4.12 Additional information for Class C waste shipments shall be provided in accordance with Attachments 24.4 and 24.5. Class C documentation must be received by the Barnwell Licensing Department prior to shipment departure and specific approval by SC DHEC is required prior to disposal.

3.4.13 Irradiated Hardware Liner Inventory Log, see Section 16.

3.4.14 Shipments with packages containing waste from more than one generator must comply with Section 21.

3.5 Shipment Prior Notification

3.5.1 Shippers shall comply with all notifications (written and telephone) in accordance with Step 5.3.

3.5.2 Shippers making waste shipments containing Radioactive Material Quantities of Concern (RAMQC) to the Barnwell Site shall comply with the notification requirements of Reference 2.8 and Section 22.

3.5.3 Shippers making waste shipments containing Category 1 and/or Category 2 nationally tracked sources to the BDF shall comply with the requirements of Reference 2.3 and Step 13.4 and Section 23 of this criteria.

3.6 Shipment Documentation

The following documents shall accompany the shipment. Other documents may be required based on type of shipment being made.

3.6.1 The Barnwell Waste Management Facility Uniform Low-Level Waste Manifest. This includes Forms 540/540A, 541/541A, and 542/542A, as appropriate. Detailed instructions for completing these forms are provided in Attachment 24.3.

Note: At shipment departure, a copy of the waste manifest must be mailed, faxed, or emailed to CNS. Mail copy to Chem-Nuclear Systems LLC, Licensing, 740 Osborn Road, Barnwell, SC 29812 or fax to 803-259-1744.

3.6.2 SC DHEC Radioactive Waste Shipment Prior Notification and Manifest Form (SC DHEC 802 Form).

Note: A SC DHEC 802 Form is required for all waste shipments greater than 75 cubic feet and/or greater than 1 curie and for radioactive waste required to be transported by exclusive-use conveyance per DOT regulations.

3.6.3 SC DHEC Radioactive Waste Shipment Certification Form (SC DHEC 803 Form).

- 3.6.4 Complete isotopic analysis printout or equivalent for aqueous filter media, filters, and resins (See Step 13.16).
- 3.6.5 Documentation required for Class "C" waste shipment (See Section 15. and Attachment 24.4).
- 3.6.6 Written statement of any unusual hazards and/or precautions that must be taken (Refer to Step 13.14).
- 3.6.7 High Integrity Container Certification (Refer to Step 13.15).
- 3.6.8 A DOE/NRC Form 741 for Special Nuclear Material (SNM), when required.
- 3.6.9 Irradiated Hardware Inventory Liner Log (See Section 16 and Attachment 24.11), when required.
- 3.6.10 Emergency Response Sheets.
- 3.6.11 Exclusive-Use Instruction, when required.
- 3.6.12 Typical Waste Package Data Summary Form (Example), Attachment 24.10 and Section 21
- 3.6.13 Cask leak test documentation, when required.
- 3.7 **Off-Loading Schedule**
 - 3.7.1 Arriving shipments should be off-loaded in order of arrival.
 - 3.7.2 Special shipments should be off-loaded in accordance with contractual or other arrangements made in advance.
 - 3.7.3 Special casks and other shipments that require non-routine operations for off-loading may be deferred in the off-loading routine to an appropriate time for commencement of handling.
 - 3.7.4 License and criteria limitations, weather or site ground conditions, darkness, and crane availability are all key items that may cause delays or rearrangements of shipments in off-loading.
- 3.8 **Driver Check-In Procedure**
 - 3.8.1 Present shipping documents to Security Officer at Main Gate Security.
 - 3.8.2 Security Officer shall time stamp the Waste Manifest Forms.

3.8.3 Security Officer shall copy paper work and notify Licensing Department of shipment arrival. Security Officer shall provide a copy of the paperwork to the Billing Department.

3.8.4 Licensing/Appropriate Personnel will obtain the shipment documents from Security.

Note: Shippers shall ensure that carriers are briefed on the importance of delivering the shipment to the correct facility.

3.9 Delays

3.9.1 BDF shall not be responsible for transport equipment detention or special equipment demurrage charges assessed by the carrier. Payment of detention/demurrage charges shall be the responsibility of the customer.

3.9.2 BDF assumes no responsibility for transport equipment delays or special detention charges assessed by the carrier due to weather delays, improper paperwork, special casks, non-routine off-loads, delays in Class C waste disposal approvals, decontaminating vehicles containers, violation of Federal and/or State requirements, or other shipment discrepancies.

3.10 Retrievability of Disposed Material

All materials disposed of at the BDF become the property of the State of South Carolina. No provision or authority exists for material retrieval following disposal.

3.11 Equipment Storage

Loading, storage, or exchange of pallets, liners, or containers for third parties will not be accommodated at the BPF unless prior approval has been obtained by the Disposal Operation General Manager.

4. WASTE SCHEDULING

4.1 Shipment scheduling shall be performed by the waste generator or authorized Broker/Shipper.

4.2 All customers shall contact the Licensing (803-541-5013 or 5009) to schedule shipments. A CNS Shipment ID Number shall be assigned to each shipment.

4.3 At the time of initial shipment scheduling with Licensing Department, the customer will be required to provide the following information (or an estimate, which will be updated, as information becomes available):

4.3.1	Customer Name	
4.3.2	Arrival Date	
4.3.3	Activity	
4.3.4	Package Dose Rate (Highest)	
4.3.5	Volume (Total)	
4.3.6	Weight (Total)	
4.3.7	Shipment Type (i.e., Van, Cask, Flatbed)	
4.3.8	Waste Class	
4.4	Customers must update Licensing of any changes to the information provided in accordance with Step 5.3, cancellations, or other pertinent changes.	
4.5	Generators should schedule monthly waste shipments under Shipment ID Numbers by the 10 th of the month that the waste will be shipped to ensure appropriate availability of concrete vaults for immediate disposal.	
5.	PRIOR NOTIFICATION PLAN (PNP)	
5.1	General	
	The Prior Notification Plan is required by Reference 2.4 and CNS. Questions concerning SC DHEC notifications shall be directed to SC DHEC. SC DHEC 802 Form and SC DHEC 803 Form must be obtained from SC DHEC.	
5.2	Instructions	
5.2.1	Complete forms as indicated by the instructions.	
5.2.2	Shippers shall use the CNS Shipment ID Number in Item 4 (Shipment Identification Number) of the SC DHEC 802 Form.	
5.2.3	Distribute the SC DHEC 802 Form as follows:	
5.2.3.1	One copy mailed or faxed to the SC DHEC office in Columbia, South Carolina (Fax Number 803 898-0391).	
5.2.3.2	One copy mailed, faxed, or emailed to CNS Licensing Department at Barnwell (Fax Number 803 259-1744).	

	5.2.3.3	One copy to accompany the shipment.	
	5.2.4	A completed copy of the SC DHEC 803 Form shall accompany the shipment.	
5.3	PNP Notifications		
	5.3.1	CNS Licensing Department and SC DHEC must receive the SC DHEC 802 Form 72 hours prior to shipment being transported into or within the State of South Carolina.	
	5.3.2	Shippers shall keep the Licensing Department and SC DHEC informed of all data changes concerning the SC DHEC 802 Form and all shipment cancellations.	
	5.3.3	Shipment departure notification and updates shall be given to the Licensing Department when the shipment leaves the customer's facility.	
	5.3.4	The Licensing Department will update SC DHEC with the correct Shipment ID Number, if the Shipment ID Number is changed by CNS or if the shipment is delayed until the following month.	
6.	WASTE MANIFEST FORMS		
6.1	General		
	6.1.1	Unless otherwise approved by the Barnwell Licensing Department, only approved Waste Manifest Forms shall be accepted. (Attachment 24.6)	
	6.1.2	Waste Manifest Forms are available from the Licensing Department.	
	6.1.3	Waste Manifest Forms are inspected by CNS personnel and the on-site SC DHEC official prior to shipment acceptance. Other state and federal regulatory agency inspections may also be performed.	
	6.1.4	Improperly prepared Waste Manifest Forms will result in acceptance delays or refusal of the shipment and may result in additional charges.	
	6.1.5	A signed copy of the Waste Manifest Forms shall be returned to the shipper within seven days after the shipment has been accepted for disposal at the BDF.	
	6.1.6	A letter indicating that the shipment has been received will be sent to the shipper within seven days should acceptance be delayed. (e.g., inclement weather, etc.)	

6.2 Instructions

Forms shall be completed in accordance with the detailed instructions for completing these forms (located in Attachment 24.3).

6.3 Special Considerations

6.3.1 All totals shown on the Waste Manifest Form shall match all accompanying paperwork for a given shipment.

Note: SC DHEC 802 Form values must match waste manifest form values.

6.3.2 All disposal volumes, weights, radiation levels, activities, etc., shall be accurate when shipment is received for burial. The activities and weights on the continuation sheets must equal the totals listed on the manifest cover sheet. If any changes are to be made after waste has been disposed of, the generator shall make a written justification for necessity of change and an additional fee may be charged.

6.3.3 The weight listed on the Waste Manifest Forms must be as accurate as possible. This information is used by CNS Personnel for billing purposes, and to select the proper off-loading equipment for the particular package. Failure to list correct weights could result in personnel injury and/or equipment damage and/or Regulatory investigation. Discrepancies of this type could result in a substantial penalty charge.

6.3.4 To determine the container volume or displacement volume of the package, reference Section 7, Attachment 24.7.

6.3.5 The customer shall provide a written statement on or attached to the Waste Manifest Form listing any unusual hazards. (See Step 13.14)

Note: Prior to shipment, notification of unusual hazards shall be made to the Barnwell Licensing Department.

7. VOLUME AND WEIGHT MEASUREMENT CRITERIA

7.1 Disposal charges shall be based on the contract rates set in the customer agreement.

7.2 Standard shaped packages (i.e., square, rectangular, cylinder) shall be sized using routine external measurements. Displacement volumes of steel drums up to 110 gallons and standard B-25 boxes are provided in Attachment 24.7.

7.3 The volume of any odd-shaped package (i.e., with protrusions, legs, flanges, etc.) shall be agreed to by CNS Marketing, and the customer, prior to shipment. Odd-shaped packages received on Site without prior agreement of total displacement volume, shall be measured by CNS and disposal charges shall be assessed accordingly.

7.4 The maximum package size (including lifting lugs, skids, etc.) shall be 9' 4" L x 7' 6" W x 9' 2" H with a maximum package weight of 54,000 pounds.

Note: Any packages exceeding the dimensions or weight in step 7.4, shall have CNS Licensing prior approval before shipment.

Bulging boxes must maintain complete compliance with Reference 2.2.

7.5 All weights shall be accurately reported.

7.6 External brace work is included in total gross box measurements. These pieces will hold one box away from another creating void space, which cannot be utilized. In the case of bulging boxes, the measurements are taken at the bulge. (The bulge will keep the box from being "snugged" up against another and may constitute the use of additional waste disposal vaults).

7.7 Skids or pallets are not included in the measurements.

7.8 The individual container volume is rounded off to the nearest tenth of a cubic foot. (128.64 cubic feet would be 128.6 cubic feet).

7.9 Cylindrical liner measurements are based on the outside maximum diameter and the maximum planar height.

8. WASTE CLASSIFICATION AND PACKAGING

8.1 All shipments received at the BDF shall be properly classified and marked in accordance with Reference 2.1. The waste class (A-U, A-S, B, or C) shall be durably and legibly marked on top of the disposal container.

Note: Stable waste is waste that is inherently stable (i.e., metal reactor components), has been rendered stable by placement in a high integrity container, or has been rendered stable by processing with an approved solidification media. An approved media is one for which specific approval has been granted by SC DHEC. Any such processing with a media must eliminate void spaces in containers to the extent practicable. Unstable waste is all other waste that complies with all other license requirements except those listed for stable waste.

The Waste Manifest Form shall indicate the waste class as: A-U, A-S, B, or C for each disposal package listed.

All waste containers shall be filled to no less than 85% except for waste packaged in approved high integrity containers or waste comprised of irradiated metal for disposal in the slit trench.

All waste must be disposed in concrete vaults unless specifically approved by SC DHEC.

- 8.2 For Class A Unstable wastes that are processed refer to Section 14 for waste classification methodology.
- 8.3 Additional information for Class C waste shipments shall be provided in accordance with Attachment 24.5. Class C documentation must be received by the Barnwell Licensing Department prior to shipment departure (See Section 15) and specific approval by SC DHEC is required prior to disposal.
- Note: Class C Documentation should be received by the Barnwell Licensing Department two (2) working days prior to shipment arrival at the Barnwell Site.**
- 8.4 For Irradiated Hardware waste, refer to Section 16 for waste classification and notifications.
- 8.5 Radwaste containing Special Nuclear Material (SNM) shall comply with Section 13.10.
- 8.6 The package identification and other required marking and labeling shall be clearly visible on the shipping package. Special emphasis should be directed to this whenever wrapping materials are placed on the shipping package.
- 8.7 The waste classification for disposal packages that contain two or more inner packages shall be determined for each inner container. The most restrictive classification shall be indicated on the outer disposal container. (Example: A High Integrity Container Overpack containing one Class A Stable drum and one Class C drum shall be marked as Class C waste).
- 8.8 Cardboard boxes, corrugated paper drums, etc., are NOT acceptable containers for disposal.
- 8.9 Unless otherwise authorized by the Barnwell Licensing Department, waste shall be contained in wooden, plastic, or metal containers or SC DHEC approved high integrity containers.

Note: Disposal containers shall not be corroded to the point of container degradation. Containers having minor surface rust are acceptable, but shall meet as a minimum, the general packaging requirements of the DOT.

- 8.10 All wooden boxes shall be banded with metal bands.
- 8.11 Boxes shall be of waterproof construction or properly covered during transit.
- 8.12 All boxes must be equipped with skids or non-returnable lifting devices.
- 8.13 Drums or other containers filled with non-radioactive materials shall NOT be used for shielding. New containers may be used as dunnage.
- 8.14 Any supplemental shielding, interior or exterior to the shipping container shall have approval from the Barnwell Licensing Department prior to shipping.
- 8.15 A van is not considered as a shipping container.

9. VAN SHIPMENTS

Note: Shipments arriving at the BDF must be properly blocked, braced, and secured. Shippers should verify that their shipments meet the applicable requirements cited in Reference 2.9

9.1 Drums

- 9.1.1 Open-top vans or flatbed trailers are the preferred method for shipment of drums.

Note: Vans with hydraulic lift gates are not acceptable without prior approval from the Barnwell Licensing Department.

- 9.1.2 Drums weighing 1,000 pounds or less shall not be shipped on pallets without prior approval.
- 9.1.3 Drums exceeding 1,000 pounds shall be palletized or equipped with appropriate lifting devices, which have been approved by the Barnwell Licensing Department before shipment.
- 9.1.4 Drums of different sizes shall be segregated within the same shipment.
- 9.1.5 Drums shall not be placed on their sides.
- 9.1.6 Drum rings and bolts shall be properly secured and be structurally strong enough to support the weight of the drum while off-loading.

- 9.1.7 Drums with lever-lock closure devices shall have prior approval from the Barnwell Licensing Department prior to shipment departure.
- 9.1.8 Drums shall comply with Reference 2.2. Bulging lids shall not exceed height of closure ring; bulging bottoms shall not extend below bottom ring of drums.
- 9.1.9 Drums may be double stacked with proper bracing, provided the heavier drums are on the bottom.
- 9.1.10 Class A Stable, Class B, and Class C waste shall be segregated from Class A unstable waste in the same shipment.
- 9.1.11 Small drums should be stacked in reasonable quantities so that a Radwaste Technician may remove the highest container without need of a platform.
- 9.2 **Packages Weighing Less Than 8,000 Pounds**
 - 9.2.1 Each package shall have a minimum clearance of three inches from the van walls.
 - 9.2.2 Packages shall be elevated with skids from the van floor and accessible to a forklift. The use of two 2" X 4" boards nailed together is acceptable.
 - 9.2.3 Each package shall have a top clearance of at least twelve inches in a closed van.
 - 9.2.4 Steps 9.2.1 through 9.2.3 are not applicable to drums.
 - 9.2.5 Dunnage used to establish spacing is considered sacrificial.
- 9.3 **Packages Weighing More Than 8,000 Pounds**
 - 9.3.1 Packages shall be provided with properly attached lifting devices.
 - 9.3.2 Lifting devices shall be secured to the top of packages and be readily available for easy access.
 - 9.3.3 Packages shall not be shipped in closed, hardtop vehicles without prior approval from the Barnwell Licensing Department.
 - 9.3.4 Each package shall have a minimum clearance of three inches from the van walls.

9.3.5 Shipments with boxes weighing more than 8,000 pounds and drums shall be segregated. Lifting devices shall have prior approval from the Barnwell Licensing Department prior to shipping.

9.4 Mixed Shipments (Drums, Boxes, Liners, etc., Containing Class A, B, and C Waste)

9.4.1 Mixed shipments shall comply with Steps 9.1 through 9.3 as applicable.

9.4.2 Only Class A Unstable waste shall be segregated from Class A Stable, Class B, and Class C waste when shipped together on the same shipment.

9.4.3 When Class A Unstable waste is on the same shipment with Class A Stable, Class B, and/or Class C waste, the shipping papers shall list the location of the waste in the shipment.

Example: "Class A Unstable Waste located in the front with the Class B in the rear." This is to be indicated on the bottom of the Waste Manifest Form (if using the Form 540, in the consignee use only section).

9.4.4 Do not stack drums on boxes or boxes on drums.

9.4.5 Drums or boxes may be loaded in the forward section of the van with definite segregation of the two types of containers. (Preferably drums loaded in forward section of van).

9.4.6 Improperly mixed shipments shall result in an additional off-loading charge or refusal of the shipment.

9.5 Less Than Full Load Shipment

Shippers shall ensure that carriers are briefed on the importance of delivering the shipment to the correct Facility (i.e., Disposal Site versus the Barnwell Processing Facility).

10. FLATBED TRAILER SHIPMENTS

10.1 Flatbed trailer shipments shall comply with Step 8.0 as applicable.

10.2 Packages with attached lifting devices are not required to have bottom clearance.

10.3 Boxes less than 8,000 pounds and/or drums shipped on flatbed trailers must be loaded in such a manner that they may be off-loaded from the side using a forklift.

11. CASK SHIPMENTS

11.1 Customers using an NRC licensed cask not owned by *EnergySolutions* shall ensure that *EnergySolutions* is a "Registered User" of the licensed cask prior to shipment to the BDF. This applies to all shipments requiring licensed packages.

11.2 Third party cask documents (C of C, SAR, handling and maintenance procedures, and drawings) shall be made available prior to shipment of the cask to the BDF.

11.3 All shipments shall strictly comply with the applicable Certificate of Compliance and/or the cask handling procedures for the cask in use (lid torquing, sealing gaskets, weight restriction, shoring requirements, etc.).

Note: Empty casks returned to CNS shall be shipped in accordance with Step 12.4.3.

11.4 Failure to observe appropriate requirements shall result in the submission of noncompliance information to the appropriate regulatory agency.

11.5 Liners containing "EnergySolutions Grapple Bails" are to be identified on Waste Manifest Form 541/541A, Item 6.

Note: Liners containing non-EnergySolutions grapple bails must have appropriate lifting cables attached in accordance with Step 11.7.

11.6 All drums shall be palletized and pallets shall have proper lifting devices attached. Boxes shall be equipped with appropriate lifting devices or palletized.

Note: Drums with dose rates greater than 1 R/hr shall be shipped in a cask on pallets and will be disposed with the pallet.

11.7 Disposal container and/or pallet shall have the lifting device secured at the top of the container(s). This is to prevent the cable from becoming caught under or between the container(s) or pallet.

Note: Lifting devices shall be of sufficient length to allow retrieval and crane hook-up without physically entering the cask. The Barnwell Licensing Department shall be notified prior to shipment of any lifting device supplied with the disposal container that has been altered, removed, or replaced.

11.8 For shipments consisting of high integrity container overpacks, the pallets on which the overpacks are placed are considered sacrificial since the pallets are used for proper placement in the concrete waste disposal vaults.

- 11.9 When using pallets, the containers shall be positioned to remain balanced and stable on the pallet when lifted clear of the cask.
- 11.10 Class A Unstable waste shall not be placed on the same pallet with Class A Stable, Class B, or C waste without prior approval from the Barnwell Licensing Department.
- 11.11 When tall, slender containers (i.e., demineralizers) are loaded on a pallet inside the cask, the containers shall be tied or secured together at the tops to prevent containers from falling off the pallets during off-loading.

Note: This is not required for a single tier of drums, i.e., 55-gallon, 83-gallon, etc., which are placed on a pallet.

- 11.12 Palletized drums inside a cask shall be loaded to prevent movement in such a manner that any shifted position of drums on the pallet will not increase radiation levels measured outside the cask. (Dunnage shall be removable with palletized loads.)
- 11.13 A shipment consisting of individual disposal containers not on pallets shall have attached to each container a lifting device that will allow off-loading by a single lift.

Example: Shipping 4 demineralizers without a pallet would require the use of a "D" ring with a 4-part spreader (spider). Each lifting leg of the spreader would be attached to one of the disposal containers lifting slings.

- 11.14 Lifting slings attached to disposal containers or pallets are considered sacrificial and are not returnable.

12. CONTAMINATION LIMITS OF PACKAGE/VEHICLE

12.1 General

- 12.1.1 All shipments received at the Barnwell Site shall comply with contamination control limits of Reference 2.2.
- 12.1.2 Loose contamination on and between packages that may be obscured by various barriers (i.e., impact limiters, base plates, etc.) shall be considered. Contamination limits for the package, the barrier and the vehicle shall comply with References 2.2 and 2.5.
- 12.1.3 The receipt of excessive surface contamination on containers in casks or otherwise, is very undesirable from the standpoint of site cleanliness and contamination control. Customers should use all means at their disposal to ship containers with minimal surface contamination.

12.1.4 Notify the Barnwell Licensing Department prior to shipment of any smearable contamination on the disposal container and/or cask interior surface exceeding 50,000 dpm/100 cm² beta-gamma and/or 2200 dpm/100 cm² alpha.

12.1.5 Disposal containers that have been wrapped to prevent the spread of loose contamination shall have, prior to shipment, approval from the Barnwell Licensing Department.

Note: The customer shall notify the Barnwell Licensing Department prior to departure of any shipment, which has the potential for causing airborne contamination under normal handling circumstances and/or has contamination exceeding the limits stated in Step 12.1.4. Failure to provide timely information may result in substantial surcharges or refusal of the shipment.

12.1.6 Waste outside of their disposal containers and/or foreign objects found in shipping casks or other transport vehicles are not acceptable and are subject to the requirements specified in Section 20 of this criteria.

12.2 Floor Covering

Plywood or other materials that are placed over the transport vehicles flooring, for contamination control shall be considered sacrificial, but will not be considered part of the burial volume. Time and/or supplies for floor covering removal will be chargeable.

12.3 Decontamination Prior to Release

Vehicles exiting the BDF shall be decontaminated to release limits described in Step 12.4 prior to release. Charges for decontamination services to comply with these levels shall be assessed as necessary.

12.4 Contamination Release Limits for Vehicles Exiting the Barnwell Site

12.4.1 Enclosed vehicles used solely for the transport of radioactive materials (Exclusive Use) and properly marked "For Radioactive Materials Use Only", in accordance with Reference 2.2:

12.4.1.1 Fixed contamination shall not exceed 10 mrem/hr on contact with the interior surface or 2 mrem/hr at one meter from the interior surface.

12.4.1.2 Fixed contamination shall not exceed 0.5 mrem/hr at any exterior accessible surface.

- 12.4.1.3 Removable contamination shall not exceed 220 dpm/100 cm² alpha and 2200 dpm/100 cm² beta-gamma in the interior or on the exterior of the vehicle.
- 12.4.2 Enclosed vehicles used solely for transport of radioactive material (Exclusive Use) and NOT marked according to Step 12.4.1.
 - 12.4.2.1 Fixed contamination shall not exceed 0.5 mrem/hr at any accessible surface.
 - 12.4.2.2 Removable contamination for beta-gamma shall not exceed 220 dpm/100 cm².
 - 12.4.2.3 Removable contamination for alpha shall not exceed 22 dpm/100 cm².
- 12.4.3 Empty Casks
 - 12.4.3.1 Fixed contamination shall not exceed 0.5 mrem/hr at any accessible exterior surface unless cask is properly labeled and a completed Radioactive Shipment Record (RSR) accompanies the cask.
 - 12.4.3.2 Removable external contamination for beta-gamma shall not exceed 2200 dpm/100 cm².
 - 12.4.3.3 Removable external contamination for alpha shall not exceed 220 dpm/100 cm².
- 12.4.4 Vehicles or Items for Unconditional Release
 - 12.4.4.1 Fixed contamination shall not exceed 0.1 mrem/hr at any accessible surface.
 - 12.4.4.2 Removable beta-gamma contamination shall not exceed 220 dpm/100 cm².
 - 12.4.4.3 Removable alpha contamination shall not exceed 22 dpm/100 cm².

13. SPECIAL CATEGORIES

13.1 Dry Active Waste

Dry Active Waste (DAW) consists of paper, plastics, contaminated metals, soil, building rubble, air filters, etc.

13.1.1 Dry Active Waste (DAW) must be packaged and classified for disposal in accordance with Reference 2.1 and Section 8.

13.1.2 All waste containing isotopes with greater than 5 year half-lives having a total specific activity greater than or equal to 1 $\mu\text{Ci/cc}$ requires stabilization.

13.2 Biological Material

13.2.1 Plants, animals, and by-products are considered biological material. Glassware, etc., that at one time contained these materials may also be considered biological. All biological waste shall be packaged in accordance with this section.

Note: Biological waste containing isotopes with greater than 5 year half-lives having a specific activity of greater than or equal to 1 $\mu\text{Ci/cc}$ must be stabilized. Also, if the sum of fractions for the isotopes with a greater than 5 year half life exceeds 1 the waste must be stabilized.

13.2.2 The inner container having a capacity of 55-gallons or less shall be in good condition and shall as a minimum comply with the DOT's general design requirements for radioactive material packaging.

13.2.3 The inner container shall have a watertight liner (i.e., polyethylene or equivalent) of at least 4 mils thickness.

13.2.4 The biological material shall be placed in the inner container and thoroughly layered with absorbent and slaked lime.

13.2.4.1 The lime used shall be commercially available slaked lime.

13.2.4.2 The absorbent used should be agricultural grade four vermiculite or medium grade diatomaceous earth.

Note: Other absorbent materials may be acceptable with SC DHEC approval. Other absorbents currently approved are Chemsil 3030, Water Works Crystals SP-100, Water Works Crystals Long Grain, and Waste Lock 770.

- 13.2.4.3 The addition of lime and absorbent to biological material should be in a ratio of one part lime to ten parts absorbent to thirty parts biological material.
- 13.2.4.4 The addition of formaldehyde is strictly prohibited.
- 13.2.5 The watertight liner shall be hermetically (airtight) sealed by taping, tying, or heat-sealing.
- 13.2.6 The seal on the inner container is crucial to proper containment and made in the following manner:
 - 13.2.6.1 The ring-and-bolt-equipped containers shall be closed with an appropriate wrench.
 - 13.2.6.2 Lever locks are not acceptable.
- 13.2.7 The inner container shall be placed upright in an outer container.
- 13.2.8 The outer container shall meet the DOT's general design requirements for radioactive materials packaging.
- 13.2.9 The bottom of the outer container shall be covered with a minimum of four inches of absorbent material.
- 13.2.10 After the inner container(s) is/are placed in the outer container, the void space shall be filled with additional absorbent material.
- 13.2.11 Unless otherwise approved by SC DHEC, the volume of the outer container must be at least 1.5 times the volume of the inner container.
- 13.2.12 A refrigerated van shall be used to ship biological radwaste between April 1 and October 1, if transit time will exceed 48 hours from the time the biological radwaste is first removed from cold storage until arrival at the Site.

13.3 Gaseous Waste

13.3.1 Krypton 85 and Xenon 133 are acceptable in DOT specification cylinders or NRC approved sealed sources with internal pressures less than 1.5 atmospheres and less than 100 curies per container.

13.3.2 Sealed Tritium gas sources are acceptable provided:

13.3.2.1 The source is approved by the U.S. Nuclear Regulatory Commission, or an agreement state.

13.3.2.2 The maximum activity per disposal container must not exceed 1000 curies.

13.3.2.3 The sources/devices must be received intact to provide additional physical protection to the primary tritium source containment.

13.3.2.4 Sources requiring stabilization as determined by waste classification, (using the volume of the sealed source only), are placed in high integrity containers or encapsulated with an appropriate stabilization media.

13.3.2.5 The internal pressure of each source does not exceed 1.5 atmospheres.

13.3.2.6 Methods used for stabilizing these sources shall be approved by the Barnwell Licensing Department prior to shipment.

13.4 Sealed Sources or Special Form Radioactive Materials

13.4.1 Sealed sources or special form radioactive material must have approval from the Barnwell Licensing Department, and may require specific approval from SC DHEC prior to acceptance for disposal. An example request for approval is located in Attachment 24.8.

Note: See Section 23 regarding additional requirements for Nationally Tracked Sources.

13.4.2 The smallest allowable package will be a five-gallon container.

13.4.3 SC DHEC has placed the following container limits for source form radionuclides:

<u>Radionuclide</u>	<u>Maximum Activity per Container</u>
Ra-226	50 μ Ci
I-129	150 μ Ci
Am-241	500 μ Ci
Alpha > 5yrs	500 μ Ci
Tc-99	6 mCi
C-14	15 mCi
Pu-241	16 mCi
Cm-242	90 mCi

Note: If there are multiple radionuclides to be placed into an individual package, unity will be considered based upon these limits.

- 13.4.4 Cement encapsulation media used for the encapsulation of sealed sources to achieve stability may be acceptable provided the encapsulation method is approved by the Barnwell Licensing Department.
- 13.4.5 The encapsulation method must consist of a minimum of 4 inches of structural grade cement (2500 p.s.i. or greater) that surrounds the sources on all sides.
- 13.4.6 Waste classification for sealed sources is based on the actual source volume. Volumes for source housings or encapsulation media shall not be included.
- 13.4.7 Small quantity sources with radionuclides other than Radium and Transuranics with activities, which do not exceed Class A limits (determined using a source volume of 1 cubic centimeter), may be disposed as Class A waste packaged as DAW.

Note: Waste containing isotopes with greater than 5 year half-lives having a total specific activity greater than or equal to 1 μ Ci/cc requires stabilization. Also, if the sum of fractions for the isotopes with a greater than 5 year half life exceeds 1 the waste must be stabilized.

13.5 Liquid Radioactive Waste

- 13.5.1 No liquid waste or solid waste containing liquids shall be received at the BDF.

13.5.2 Solidified liquid waste may be accepted provided it is solidified with one of the following solidification media:

13.5.2.1 Vinyl Ester Styrene

13.5.2.2 Cement

13.5.2.3 Bitumen

13.5.2.4 Vinyl Chloride

13.5.2.5 Aquaset II-H (Class A-U waste only)

13.5.2.6 Petroset H (Class A-U waste only)

13.5.2.7 MetalPlex III (Class A-U waste only)

Note: Solidified oil is not acceptable for disposal. (See Step 13.8)

13.5.3 Liquid waste containing isotopes with greater than 5 year half-lives having a total specific activity greater than or equal to 1 $\mu\text{Ci/cc}$ requires stabilization. Also, if the sum of fractions for the isotopes with a greater than 5 year half life exceeds 1 the waste must be stabilized.

13.5.4 Hazardous organic solutions, solidified or otherwise, are not acceptable for disposal at the BDF.

13.6 Wastes Containing Free Standing Liquids

13.6.1 Evaporator bottoms or concentrates, residues, sludges, or other waste which may contain free standing liquids must be solidified in accordance with Condition 33 of License 097, Reference 2.1, and meet the requirements as specified in Condition 32 of License 097, Reference 2.1.

13.6.2 Wastes that have been processed to contain no freestanding water and are not free flowing are acceptable for disposal when processed by a method specifically approved by SC DHEC prior to shipment.

13.7 Scintillation Products and Containers

13.7.1 Toluene, xylene, dioxane, scintillation liquids which exhibit hazardous properties or other organic liquids or solids with similar chemical properties are prohibited except as specified below:

- 13.7.1.1 Containers, which have contained any of the liquids mentioned above, are acceptable for disposal after treatment as specifically authorized by SC DHEC.
 - 13.7.1.2 The ash and/or residue from the incineration of these wastes are acceptable in accordance with Condition 45 of License 097, Reference 2.1.
 - 13.7.2 Solidified or processed waste containing non-hazardous scintillation products may be acceptable, provided the scintillation products have been approved by SC DHEC.
 - 13.7.2.1 Scintillation products that have received SC DHEC approval shall be identified by product name on the shipment manifest.
 - 13.7.2.2 The following scintillation products have been approved by SC DHEC for disposal: Ecoscint A, Ecoscint O, Opti -fluor, Ultima Gold, Ultima Gold LLT, Ready-Safe, Ready Cap, Ready Filter, Meltilex, and Beta Plate Scint XSC/9200. Additional products may be acceptable, provided they are approved by SC DHEC.
- 13.8 **Oil**
 - 13.8.1 Petroleum based oils, regardless of waste form, are not acceptable for disposal at the BDF.
 - 13.8.2 Waste containing incidental or trace amounts of absorbed oil are acceptable, provided they do not exceed one percent (1%) of the waste volume in a container; however, waste streams cannot be blended or mixed to obtain compliance.
 - 13.8.3 Synthetic oils may be acceptable provided they have been approved by SC DHEC.
- 13.9 **Pyrophoric Materials or Flammable Solids**
 - 13.9.1 Pyrophoric or flammable solid material contained in waste shall be made inert to prevent self-ignition during transport and disposal.
 - 13.9.2 The inerting process shall be approved by the Barnwell Licensing Department prior to shipping.
 - 13.9.3 No material that might react violently with water or moisture shall be accepted for disposal at the BDF.

13.10 Special Nuclear Material (SNM)

Note: Special Nuclear Material (SNM) means plutonium (Pu), U-233, or uranium enriched in U-233 or U-235.

- 13.10.1 All SNM waste shall be packaged and reported in accordance with Reference 2.1, 2.3, and Section 3.6 of this procedure.
- 13.10.2 Waste containing plutonium must meet the requirements of Condition 40 of Reference 2.1. Waste not meeting these requirements will require specific approval by SC DHEC.
- 13.10.3 The surface area on any side or projected plane of a package containing U-233, U-235, Pu shall be 2 ft² or greater. Only 55-gallon drums and larger packages are acceptable without prior approval from Barnwell Licensing Department.
- 13.10.4 Shippers having individual packages in excess of 100 grams of U-235 shall have on file with the Barnwell Licensing Department a statement indicating the percent confidence in their shipping values.
- 13.10.5 The Barnwell Licensing Department shall be notified prior to shipment of SNM packages exceeding 100 grams of U-235 in which the confidence in shipping value is less than 95 percent.
- 13.10.6 No single package/shipment shall contain more than 200 grams of U-233, 350 grams of U-235, or 200 grams of Pu. For packages containing a combination of U-233, U-235 or Pu, the sum of the ratios of the individual quantity of each SNM radionuclide to the quantity specified above for that radionuclide shall not exceed unity.

13.11 Hazardous Chemicals

- 13.11.1 Waste material containing hazardous chemicals/agents and radioactive materials shall be acceptable for disposal only when the radiological hazard clearly exceeds the toxic chemical/agent hazard.

Note: Mixed waste requirements are specified in Section 13.20.

- 13.11.2 All shipments shall comply with Reference 2.1 regarding the assessment of chemical versus radiological hazards.

- 13.11.3 When any determination has been made as to the classification of the hazard, an independent evaluation of the radiological, biological, and chemical hazards shall be performed and the reports shall be submitted to the Barnwell Licensing Department for review prior to shipment.
- 13.11.4 CNS shall receive, review, and maintain on file all reports of evaluations for SC DHEC review.
- 13.11.5 Upon completion of review and comment, the reports if necessary, will be submitted by CNS to SC DHEC for evaluation as to the acceptability of the waste material for disposal.

13.12 Transuranics (Elements with Atomic Numbers greater than 92)

- 13.12.1 Wastes containing transuranic nuclides are acceptable, provided the following conditions are met.
 - 13.12.1.1 The concentration limits specified in Reference 2.1 are not exceeded.
 - 13.12.1.2 The transuranic nuclides are evenly distributed within a homogeneous waste form.
 - 13.12.1.3 The transuranic content is incidental to the total activity. Incidental is defined as up to one percent (1%) of the total activity.

Note: Plutonium-241 is exempt from the one percent incidental transuranic activity criteria provided it is not the only transuranic in the waste. However, it must be considered when classifying the waste. Wastes containing only transuranics or plutonium-241 are not acceptable for disposal unless specifically approved by SC DHEC.

- 13.12.1.4 If the limits of Reference 2.1 for transuranics are exceeded, SC DHEC prior approval is required.
- 13.12.2 Each transuranic nuclide must be identified on the Waste Manifest Form.
- 13.12.3 Packages containing transuranics, which are plutonium isotopes must comply with Section 13.10.
- 13.12.4 Smoke or gas detectors containing Americium-241 foils, which exceed the limits specified in Reference 2.1 maybe acceptable for disposal provided the entire detector is received for disposal.

- 13.12.5 In-core detectors or other such devices, which contain transuranics require approval by the Barnwell Licensing Department prior to shipping.

13.13 Uranium Oxide

Uranium oxide shipments are subject to heavy external contamination of containers. Precautions shall be taken to ensure that the shipping container contamination will be less than the limits specified in Reference 2.2.

13.14 Unusual Hazards

- 13.14.1 The shipper of radioactive material shall notify the Barnwell Licensing Department prior to departure of any shipment in which the possibility exists for unusual hazards.
- 13.14.2 Barnwell Licensing shall obtain approval of the Disposal Operations General Manager, or designee before authorizing the departure of any shipments with unusual hazards to the BDF.
- 13.14.3 The shipper shall provide a written statement on or attached to the Waste Manifest Form containing information as to unusual hazards.
- 13.14.4 Wind, weather, or other unusual circumstances may delay off- loading this type shipment.
- 13.14.5 Unusual hazards include, but are not limited to, the presence of neutron sources or neutron emitters in the shipment, spills in or on shipping containers or vehicles, excessive external contamination levels on disposal containers (see Step 12.1.4), any non-routine waste processing event, any damage which has occurred to a disposable container or lifting device, etc.

13.15 High Integrity Containers

- 13.15.1 Only high integrity containers approved by SC DHEC are acceptable for burial at the BDF. Shippers shall ensure that a copy of the Certificate of Compliance (C of C) for the approved high integrity container as issued and amended by SC DHEC is on file with the Barnwell Licensing Department.
- 13.15.2 The Barnwell Licensing Department shall have signed documentation on file from the shipper or notification from SC DHEC that the shipper has received and will adhere to the requirements of the C of C.

- 13.15.3 A certification that the shipper has stored, handled and used the high integrity container in accordance with the C of C shall accompany the shipment to the BDF.

13.16 Filter Media/Filters/Resins

For each shipment containing resin or other aqueous filter media (including filters), a complete isotopic analysis shall be provided with the shipment. The analysis shall identify the following:

- 13.16.1 Disposal package number

- 13.16.2 Waste description

- 13.16.3 Radionuclides present

Note: Filters (i.e., fuel pool filters), which have the potential to contain activated metal in the form of shavings, must be classified with consideration given to concentrations of ^{59}Ni , ^{94}Nb , ^{14}C AND ^{63}Ni in activated metal.

- 13.16.4 Total curie content

- 13.16.5 Resin/filter media volume (cc or ft³)

- 13.16.6 Indicate the number of filters in the container.

- 13.16.7 The specific activity of each radionuclide and the total radionuclide concentration shall be expressed in microcuries/cubic centimeter or curies/cubic meter and transuranic radionuclides in nanocuries/gram.

- 13.16.8 Waste classification for resin, filter media, and filters must comply with Reference 2.1 and Reference 2.6.

- 13.16.9 Resin, filter media, or filters that are classified as Class C waste must comply with Section 15.

Note: These requirements are not applicable to air filters. (See Section 13.1)

13.17 Slit Trench Shipments

- 13.17.1 Cask shipments which are required to be off-loaded using the horizontal off-load technique shall have approval of the Disposal Operations General Manager, or designee prior to shipping.

- 13.17.2 Horizontally off-loaded shipments shall have the liner removal device approved by the Disposal Operations General Manager or designee, prior to shipping.

13.18 Chelating Agents

- 13.18.1 Waste containing chelating agents with concentrations in its final waste form greater than 0.1 percent but less than 8 percent by weight is acceptable, provided it is stabilized with one of the solidification agents specified in Reference 2.1.
- 13.18.2 Waste containing chelating agents greater than 8 percent by weight, is not acceptable.
- 13.18.3 The name and percent of chelating agents in the waste shall be listed on the Waste Manifest Form.
- 13.18.4 Dewatered waste containing chelating agents in concentrations ranging from 0.1 to 8.0 percent by weight will be accepted for disposal provided the following are met.
- 13.18.4.1 The waste is placed in a high integrity container (HIC).
- 13.18.4.2 The waste contains less than 1% free standing liquid by waste volume.

13.19 Lead

Non-radioactively contaminated lead specifically used for shielding purposes may be acceptable for disposal with prior approval by the Barnwell Licensing Department. Information requested on Attachment 24.9 shall be provided for evaluation.

13.20 Mixed Waste

- 13.20.1 No mixtures of radioactive waste and hazardous waste as defined by Title 40 Code of Federal Regulations (CFR) Part 261 and S.C. Hazardous Waste Management Regulation 61-79.261 will be accepted.
- 13.20.2 A mixture of radioactive waste and waste which was classified as hazardous solely because it exhibited one or more of the hazardous characteristics defined in 40 CFR 261 Subpart C, but has been treated in a manner such that it no longer exhibits any of the characteristics, will be reviewed for acceptance on a case-by-case basis. As required by 40 CFR 261.24, the Toxicity Characteristic Leaching Procedure shall be used.

- 13.20.3 A description of the treatment process and results of the analytical tests of the final waste shall be submitted to the Barnwell Licensing Department for evaluation prior to shipment.

13.21 Polychlorinated Biphenyls (PCB's)

- 13.21.1 In accordance w/ 40 CFR Part 761 – PCB's MANUFACTURING, PROCESSING, DISTRIBUTION IN COMMERCE, AND USE PROHIBITIONS, radioactively contaminated non-liquid waste containing < 50 ppm PCB's may be acceptable for disposal with prior approval from the Barnwell Licensing Department.

- 13.21.1.1 The Barnwell Licensing Department shall be provided, prior to shipment, documentation or analytical results from the shipper substantiating the level of PCB contamination is < 50 ppm.

- 13.21.2 Radioactively contaminated PCB bulk product waste as defined in Sections 13.21.2.1 & 13.21.2.2 may be acceptable for disposal with prior approval from the Barnwell Licensing Department.

- 13.21.2.1 Per §761.62(b)(1)(i), plastics (such as plastic insulation from wire or cable; radio, television and computer casings; vehicle parts; or furniture laminates); preformed or molded rubber parts and components; applied dried paints, varnishes, waxes or other similar coatings or sealants; caulking; Galbestos; non-liquid building demolition debris; or non-liquid PCB bulk product waste from the shredding of automobiles or household appliances from which PCB small capacitors have been removed (shredder fluff).

- 13.21.2.2 Per §761(b)(1)(ii), other PCB bulk product waste, sampled in accordance with the protocols set out in Subpart R of 40 CFR Part 761, that leaches PCB's at less than 10 µg/L (10 ppb) of water measured using a procedure used to simulate leachate generation.

- 13.21.2.3 The Barnwell Licensing Department shall be provided written notice stating that the PCB bulk product waste may include components containing PCB's at > 50 ppm based on analysis of the waste in the shipment or application of a general knowledge of the waste stream (or similar material) which is known to contain PCB's at those levels, and that the PCB bulk product waste is known or presumed to leach < 10 µg/L PCB's.

- 13.21.3 No other PCB's or PCB items than those described above will be accepted for disposal. Questions regarding PCB's should be directed to the Barnwell Licensing Department.

13.22 Asbestos

- 13.22.1 Packages containing radioactively contaminated asbestos waste (0.1% or greater by weight) shall be identified as asbestos under the waste description of the Waste Manifest Form and continuation sheet.
- 13.22.2 OSHA Asbestos standard 29 CFR 1910.1001 requires affixment of warning labels on waste packages containing asbestos.

13.23 Radium Wastes

Waste containing Radium are prohibited except as specified below:

- 13.23.1 Radium contained in solid homogeneous waste forms in which the Radium activity is incidental ($\leq 1.0\%$) to the total activity and the concentration of Radium has not been technologically enhanced. The classification of this waste shall be in accordance with Condition 31 of License 097, Reference 2.1.
- 13.23.2 Radium contained in self-luminous dials, hands of dials, timepieces, compasses, and electron tubes provided that the entire device is received and disposed.
- 13.23.3 Radium contained in biological research waste. The classification of this waste shall be in accordance with Condition 31 of License 097, Reference 2.1.
- 13.23.4 Radium sources which have been specifically approved by the Department. Sealed source approvals and processing shall be accomplished in accordance with Step 13.4.

14. CLASS A UNSTABLE PROCESSED WASTE

Note: This section applies to generators and processors who process waste prior to shipment for disposal. This applies only to Class A Unstable Waste.

Note: Any waste received by a processor as Class A Stable, Class B, or Class C must meet the stability requirements prior to disposal and the container must be classified using the highest waste classification in the container.

- 14.1 The following methodology shall be used for Classification of Similar and Dissimilar Class A Unstable Waste Types for shipments to BDF.
 - 14.2 “Similar or homogenous” wastes are defined as waste with the same physical characteristics (e.g. soil, ion exchange resins), contaminated trash waste (DAW), or incinerator ash. Other waste may be considered with the approval of the Barnwell Licensing Department and SC DHEC.
 - 14.3 For waste that is not “similar or homogenous” the classification of the waste must be determined by calculating the activity concentration based on the “as processed” waste volume for each generator and waste stream. For “similar or homogenous” wastes averaging may be performed over each waste type under the following conditions.
 - 14.4 The activity concentrations in each waste stream as received from the generator prior to processing must not exceed the Class A Unstable limits.
 - 14.5 The activities may be averaged over the combined volume, after processing, of each similar or homogenous waste type. This activity must not exceed the Class A Unstable limit.
 - 14.6 The following information must be provided by the waste processor on the Uniform Low-Level Radioactive Waste Manifest Form 542 (See Attachment 24.3). For each generator, a list of the radionuclides and their activities, and the waste volume prior to processing. For each “similar or homogenous” waste type in each container, the radionuclides and their activities, and volume after processing.
15. **CLASS C WASTE SHIPMENTS**
- 15.1 Class C waste shipments received at the BDF must have SC DHEC approval prior to disposal.
 - 15.1.1 Documentation for each Class C shipment must be provided to the Barnwell Licensing Department in accordance with Attachment 24.4 prior to shipment departure.
 - 15.1.2 Class C wastes shipments consisting of sealed sources or special form radioactive materials will be evaluated for approval under the provisions specified in Section 13.4.
 - 15.2 A shipment may be released for transport to the disposal site prior to disposal approval, but must have SC DHEC approval prior to disposal.

- 15.3 The Barnwell Licensing Department will review the Class C waste documentation for consistency with disposal license (Reference 2.1), Branch Technical Position on Concentration Averaging and Encapsulation (BTP), as applicable (Reference 2.6), and site disposal requirements.
- 15.4 CNS will fax a copy of the document and mail a copy to SC DHEC for their review.
- 15.5 SC DHEC will fax a response letter and mail a copy to CNS indicating the acceptance/rejection of the shipment.
- 15.6 Once approval is obtained, the waste will be disposed of.

16. IRRADIATED HARDWARE

- 16.1 An Irradiated Hardware Liner Inventory Log (Attachment 24.11) for each shipment of waste containing irradiated hardware must be completed and provided with the waste shipment manifest.
- 16.2 A Class "C" Waste Classification Record (Attachment 24.5) for each shipment of waste containing Class C irradiated hardware must be completed and submitted to the Barnwell Licensing Department in accordance with Section 15.

Note: It is recommended that the Barnwell Licensing Department be contacted before processing and/or packaging of hardware begins.

- 16.3 Waste classification for hardware must be determined using the volume and weight of the waste only. No credit for the waste container volume or container weight can be used.
- 16.4 Wastes can be classified based on the activity concentration of the highest individual component or radionuclide concentration averaging using the Barnwell Rule of 10.
 - 16.4.1 The Barnwell Rule of 10 is used to compare whole irradiated components for acceptability in blending waste within each package to meet the Class C concentration limits.
 - 16.4.2 The activity of a component such as a control rod blade, which has varying activity levels, is averaged over the entire component volume.
 - 16.4.3 Individual components exceeding Class C concentration limits can be averaged with components that are less than Class C concentration limits provided that their 10 CFR, Part 61, Table I and Table II sum of the fractions do not differ by more than a factor of 10.

- 16.4.4 All components of the same type (i.e. LPRMs) must have 10 CFR, Part 61, Table I and Table II sums of the fractions within a factor of 10 (Highest/Lowest ≤ 10).
- 16.4.5 Components of different types must have averaged batch Table I and Table II sums of the fractions within a factor of 10 (Highest Batch/Lowest Batch ≤ 10).
- 16.4.6 When concentration averaging is used, the concentration for each component or batch of components in the disposal package must be provided in Attachment 24.5.
- 16.4.7 Other wastes placed in the disposal container, which does not affect the waste classification is excluded from the Rule of 10. However, these wastes and their activities must be identified in Attachment 24.5 and reported on the shipment manifest.
- 16.5 Waste classification, using the highest individual component, may be determined using the radionuclide concentrations averaged over the entire component volume and weight.
- 16.6 The final waste classification for each waste package cannot exceed Class C.

17. LARGE COMPONENTS

Large Components are waste items that will not fit into the standard disposal vaults at the BDF. One category of large components must be disposed in concrete disposal vaults and the other category of large components can meet structural stability requirements equivalent to the concrete disposal vaults and therefore are not disposed in concrete disposal vaults. State Agency Liaison should be contacted at (803) 758-1825 regarding disposal contracts and disposal pricing for large components well in advance of the planned shipping date. CNS is responsible for all activities conducted at the BDF for the disposal of large components, including movement inside the fence, equipment for transfer to the disposal location, equipment used for stability in the disposal trench, etc. Coordination of all activities at the BDF must be done with CNS.

17.1 Large Components Disposed in Concrete Vaults

This Category of large components wastes may include oversize boxes, irregular shape packages, large pumps, etc. Case-by-case approval must be obtained from the Barnwell Licensing Department prior to shipping a large component or waste package that exceeds standard vault dimensions. Internal dimensions (ID) for standard vaults are:

Rectangular (ID)	114'' (L) x 92'' (W) x 112'' (H)
Cylindrical (ID)	86'' (H) x 84'' (D)
Slit Trench (ID)	192'' (L) x 48'' (W) x 46'' (H)

- 17.2 Concrete disposal vaults can be designed by CNS, approved by DHEC, fabricated, and used for the disposal of components requiring vaults that are too large for standard size vaults.
- 17.3 Shipment of large components to be disposed without vaults must be made in accordance with the requirements of Section 18.

18. LARGE COMPONENTS DISPOSED WITHOUT VAULTS

Disposal of components from commercial nuclear reactors are typically part of significant plant projects, which take several years from planning to completion. State Agency Liaison should be contacted at (803) 758-1825 regarding disposal contracts and disposal pricing for very large components. Shortly after the transport and disposal methods for a very large component project are confirmed, customers should make arrangements with CNS to schedule a meeting with SC DHEC to discuss the project and the preliminary plans made to date. The following documents and information must be provided to SC DHEC for review and approval.

- 18.1 The transportation plan including the transport method and conveyance, notifications to be made, the transportation routes, and estimated schedules.
- 18.2 The authorization from US DOT and/or US NRC for transportation of the component(s).
- 18.3 The waste characterization / classification methods and documentation, regardless of the resultant waste class.
- 18.4 The engineering evaluation demonstrating that the component(s) meet the structural stability requirements for the disposal site.
- 18.5 The dose assessment, which provides estimates of the personnel and fence line doses from the point of component acceptance through disposal.
- 18.6 The waste disposal trench modification plan outlining any changes from the existing trench design, access ramps, or site roadways.
- 18.7 The waste disposal plan describing how the component(s) will be accepted, handled, and disposed within the trench.
- 18.8 In additions to the requirements specified in Steps 18.1 through 18.7, the shipper must provide CNS with the following information.

- 18.8.1 The schedule for delivery.
 - 18.8.2 Component and transporter specifications.
 - 18.8.3 A listing of any special equipment that will be needed for movement or offload at the disposal site, and description of plans for procuring the needed equipment.
 - 18.8.4 Description of any unusual requirements for on-site movement, or offload, that may entail cost issues that should be resolved prior to delivery.
 - 18.8.5 Any other information required by SC DHEC or CNS that is needed for verification for compliance with regulatory requirements.
19. **SHIPMENTS NOT AUTHORIZED BY CNS RADIOACTIVE MATERIAL LICENSES**
- 19.1 If a proposed shipment does not conform to the requirements of References 2.1 or 2.2, the Barnwell Licensing Department shall be contacted by the customer and provided with detailed information on the packaging and contents of the shipment.
 - 19.2 The Barnwell Licensing Department should be contacted for the procedures for obtaining a variance. Shipments requiring variances shall be subject to a special surcharge.
20. **SHIPMENTS VIOLATING REGULATIONS OR CRITERIA**
- 20.1 The customer shall be notified by telephone of any non-conformance shipment.
 - 20.2 SC DHEC officials shall be notified of any waste shipments where a violation of applicable regulations or license conditions has been found.
 - 20.3 The customer shall have twenty-four hours to send a representative to inspect the shipment provided the violation is discovered during receipt inspection or early stages of off-loading.
 - 20.4 Twenty-four hours after customer notification, if customer inspection is waived, or if efforts to contact the customer are unsuccessful, the shipment may be off-loaded with SC DHEC approval.
 - 20.5 If deemed necessary and with the approval of SC DHEC, the shipment may be returned to the customer.

- 20.6 The customer shall be billed for any special services/equipment, detention, and additional handling charges on shipments received with violations/discrepancies. The customer will also be billed for waste disposal of any waste generated resulting from a shipment violation/discrepancy.

21. MULTIPLE GENERATOR SHIPMENTS

- 21.1 In addition to the Barnwell Waste Management Facility Uniform Low-Level Waste Manifest Form 542, shippers with packages containing waste from more than one generator must complete the Typical Waste Package Data Summary (see Attachment 24.10) or equivalent. Information required by this section may be provided in any convenient format provided the minimum required information is included.
- 21.2 The shipper of waste packages containing waste from more than one generator shall provide documentation of the following additional information for each package containing waste from more than one generator (see Reference 2.7):
- 21.2.1 The Shipment Identification Number and the Package Identification Number for each package containing waste from more than one generator.
 - 21.2.2 The Generator Name/SC Transport Permit Number for each generator with waste in the package.
 - 21.2.3 The radioactivity for each generator's waste in the package.
 - 21.2.4 The waste volume of each generator's waste in the package.
 - 21.2.5 The waste weight of each generator's waste in the package.
 - 21.2.6 The disposal volume of the container (external volume less waste volume).
 - 21.2.7 The weight of the container (without waste).
 - 21.2.8 The waste volume plus the allocated container volume proportioned to each generator with waste in the package.
 - 21.2.9 The waste weight plus the allocated container weight proportioned to each generator's waste in the container.
 - 21.2.10 The total package volume and weight (including the container) to allow crosschecking with the Form 541 data.

22. **RADIOACTIVE MATERIAL QUANTITIES OF CONCERN (RAMQC) SHIPMENT**

22.1 RAMQC shipments are shipments that contain radionuclides and quantities that are listed in Table A of Reference 2.8, which pose a concern for potential malevolent use and potential risk or consequences.

22.2 Shippers preparing waste shipments containing RAMQC to the BDF should be familiar with the shipment requirements specified in Reference 2.8.

Note: Reference 2.8 contains sensitive information that cannot be included in this document.

22.3 The shipper of a RAMQC shipment shall notify the Barnwell Licensing Department in accordance with Reference 2.8 prior to making the shipment to the BDF.

23. **NATIONALLY TRACKED SOURCES**

23.1 A nationally tracked source, as defined in 10 CFR 20.1003, refers to a sealed source containing a quantity equal to or greater than Category 1 or Category 2 levels of any radioactive material listed in Appendix E to Part 20 – “Nationally Tracked Source Thresholds”.

23.2 Effective January 31, 2009, shippers preparing waste shipments containing Category 1 and/or Category 2 nationally tracked sources to the Barnwell Site shall comply with the reporting requirements specified in Reference 2.3, Section 20.2207 and obtain prior to shipment approval from the Barnwell Licensing Department.

23.3 Prior to shipping, the shippers shall provide the Barnwell Licensing Department the following information for review and approval.

23.3.1 Shipper’s name, shipping address, license number, SC Radioactive Waste Transport Permit number, and name of individual preparing the reported information.

Note: If the shipper is a Broker, waste processor, etc., and is not the waste generator, the shipper must also provide the name, shipping address, license number, and SC Radioactive Waste Transport Permit number for each waste generator.

23.3.2 The manufacturer, model, and serial number of the source or, if not available, other information to uniquely identify the source.

- 23.3.3 The radioactive material in the source and current activity in becquerels and curies. The activity reported must be the same as the activity that will be listed on the shipment manifest.
- 23.3.4 The date the source strength is reported.
- 23.3.5 The shipping date and estimated arrival date.
- 23.3.6 The waste manifest number and the waste disposal container number.
- 23.4 The Barnwell Licensing Department will notify the shipper of each source as being either approved or disapproved for shipment to the Barnwell Site.
- 23.5 Upon source shipment arrival, the Barnwell Licensing Department will complete the source tracking transaction report as required in Reference 2.3, Section 20.2207 by the close of the next business day.
- 23.6 Upon disposal of the sources, the Barnwell Licensing Department will complete the source tracking transaction report as required in Reference 2.3, Section 20.2207 by the close of the next business day.
- 24. **ATTACHMENTS**
 - 24.1 Abbreviations
 - 24.2 CNS Telephone Numbers
 - 24.3 Instructions for Completing the Barnwell Waste Management Facility Uniform Low-Level Radioactive Waste Manifest Forms
 - 24.4 Documentation Required for Class C Waste Shipment Acceptance at the Barnwell Site
 - 24.5 Class "C" Waste Classification Record - Example
 - 24.6 Barnwell Uniform Low-Level Radioactive Waste Manifest Forms - Example
 - 24.7 Displacement of Steel Drums and Standard B-25 Boxes – Drum Volumes
 - 24.8 Example Request Approval for Sealed Source/Special Form Radioactive Material
 - 24.9 Lead Shielding Request – Example
 - 24.10 Typical Waste Package Data Summary – Example
 - 24.11 Irradiated Hardware Liner Inventory Log - Example

Attachment 24.1

Abbreviations

BTP.....	Branch Technical Position on Concentration Averaging and Encapsulation, Dated 1/17/95
C of C	Certificate of Compliance
CFR	Code of Federal Regulations
CNS	Chem-Nuclear Systems
DOE.....	Department of Energy (U.S.)
DOT.....	Department of Transportation (U.S.)
DPM	Disintegrations Per Minute
HIC	High Integrity Container
LPRM.....	Low Power Range Monitor
LSA	Low Specific Activity
NP	Not Present
NRC.....	Nuclear Regulatory Commission (U.S.)
OSHA.....	Occupational Safety and Health Administration
PCB	Polychlorinated Biphenyl
PKG.....	Package
PNP.....	Prior Notification Plan
RADWASTE	Low-Level Radioactive Waste
RWTP.....	Radioactive Waste Transport Permit
SC DHEC.....	South Carolina Department of Health and Environmental Control
SCO	Surface Contaminated Object
SITE	Barnwell Waste Management Facility
SITE CRITERIA	Barnwell Waste Management Facility Site Disposal Criteria
SM	Source Material
SNM	Special Nuclear Material
TCLP	Toxicity Characteristic Leaching Procedure

**Attachment 24.2
CNS Telephone Numbers**

Barnwell Office (803) 259-1781 Barnwell, SC
Barnwell Licensing (803) 541-5013, 5009 Barnwell, SC
24 Hour Security..... (803) 259-6069 Barnwell, SC
State Agency Liaison (803) 758-1825 Columbia, SC

BARNWELL FAX NUMBERS

Mail Room..... (803) 259-7230 Barnwell, SC
Licensing..... (803) 259-1744 Barnwell, SC
Billing..... (803) 259-1477 Barnwell, SC

Attachment 24.3

Instructions for Completing the Barnwell Waste Management Facility Uniform Low-Level Radioactive Waste Manifest Forms

Note: Shipments may be refused if contents, supporting documentation, packaging, and all other aspects of the shipment are not in compliance with Chem-Nuclear Systems State and Federal Licenses, the Barnwell Site Criteria (S20-AD-010), 49 Code of Federal Regulations, and 10 Code of Federal Regulations.

I) General Instructions for Completing Forms

1. Computer generated versions of the Barnwell Waste Management Facility Uniform Low-Level Waste Manifest forms may be acceptable, but must be approved by the Licensing Department, Barnwell Waste Management Facility.

Note: The Uniform Low-Level Radioactive Waste Manifest Forms authorized for shipments to the Barnwell Waste Management Facility have been modified and are not identical to the NRC's generic Uniform Low-Level Radioactive Waste Manifest Forms. The NRC'S generic Uniform Low-Level Radioactive Waste Manifest Forms may not be used for shipments of radioactive waste to the Barnwell Disposal Site.

2. These specific instructions for completing the Barnwell Waste Management Facility Uniform Low-Level Radioactive Waste Manifest must be strictly adhered to. Any deviations from these instructions must be approved by the Licensing Department, Barnwell Waste Management Facility. Additional pertinent information may be included if desired, but must be presented in a manner fully compliant with applicable regulations, licenses, and the Barnwell Site Criteria (S20-AD-010).
3. Unless otherwise specified, all blanks must be filled. If a blank is not to be used, the abbreviation "NA" (not applicable) may be used. In some cases, the abbreviation NP (not present) may be used (if specified in these instructions).
4. Forms should be completed in permanent dark blue or black ink. Manual printing, typing, or electronic printer may be used.
5. Continuation lines may be used for redundant entries.
6. For any numerical entry that is < 1.0 , use a 0 (zero) prior to the decimal place. For example: 0.8.

7. In general, SI units are the standard unit used on the manifest. Unless specifically instructed otherwise, SI units must be recorded followed by the conventional unit. Measurement units must be indicated for all values recorded. For example, the authorized SI unit for activity used in the manifest is the Megabecquerel and the conventional unit is the millicurie. An activity of 1,000 millicuries would be recorded as: 37000 in the MBq column and 1000 in the mCi column.

Note: Units of measurement are provided in column headings (or row headings) and need not be recorded after each numerical entry. Only those units specified on forms and in these instructions may be used. The use of parenthesis is reserved for certain key entries on these manifest forms. The use of parenthesis for the purpose of indicating a measure in conventional units is not authorized.

8. The use of scientific notation is authorized.
9. The instructions for completing continuation pages (540A, 541A, 542A) are identical to the corresponding items for the associated form.
10. The total nuclide activity (Form 541, Item 1) must be identical to the value recorded as the shipment total (Form 541/541A) and on SC DHEC 802 Form, Block Number 20.
11. The following table provides the standard SI units and the standard conventional units to be used in completing these forms. Approved conversion values are provided.

Measurement	Conventional Unit	SI Unit	Conversion
Activity	millicurie (mCi)	Megabecquerel (MBq)	1 mCi = 37 MBq
Radiation Level	millirem/hour (mrem/hr)	millisieverts/hour (mSv/hr)	1 mrem/hr = 0.01 mSv/hr
Contamination Level	disintegration per minute per 100 square centimeters (dpm/100 cm ²)	Megabecquerels per 100 square centimeters (MBq/100 cm ²)	1 dpm/100 cm ² = 1.67E-8 MBq/100 cm ²
Mass or weight	pound (LB)	Kilogram (kg)	1 lb = 0.4535924 kg
Source Material	pound (lb)	Kilogram (kg)	1 lb = 0.4535924 kg
SNM Grams	NA	grams (g)	N/A
Volume	Cubic Foot (ft ³)	Cubic Meter (m ³)	1 ft ³ = 0.02831685 m ³

II) Form Instructions

A) Form 540: Shipping Paper

- 1) Form 540 must be completed for all shipments.
- 2) The purpose of this form is to meet the DOT's shipping paper requirements. In addition to the specific instructions listed below, the shipper must ensure full compliance with all applicable requirements of 49 Code of Federal Regulations (transportation).

Item Number	Detailed Instructions- Form 540
1	Record the emergency response telephone number or numbers for use in the event of an emergency. Record the name of the organization (or individual) providing the emergency response information as required by the DOT.
2	Mark the appropriate box "yes" or "no".
3	Record the total number of DOT packages in the shipment. Note: In the case of waste packages shipped inside a larger package, (example 55 gallon drums contained in a shipping cask - with the cask acting as the "DOT" package), Item 3's entry is the total number of "DOT" packages. In the case of a cask used as the DOT shipping package - it would be "1".
4	Mark the appropriate box "yes" or "no". Record the EPA Manifest number, if applicable, otherwise record N/A. Note: The Barnwell Low-Level Waste Facility does not accept mixed or hazardous waste. For additional information, refer to the Barnwell Site Criteria (Section 13.20).
5	Record the following information: Shipper's Company Name Facility Name Facility Address SC Transport Permit Number: Record the State of South Carolina Radioactive Waste Transport Permit Number. (For example: 0000-00-97-X) Shipment Number: Record a unique number assigned by the Shipper to this shipment for tracking purpose. Contact / Telephone Number: The name/phone number of a responsible representative of the shipper's organization who can answer detailed questions concerning the shipment. Shipment ID Number: The Unique Shipment Identification Number assigned to this shipment by the Barnwell Low-Level Waste Facility Licensing Department. Collector/ Processor / Generator: Record an "X" in the appropriate box. Generators must record one of the following codes in the "Generator Type" item: A = University (academic) FC= Fuel Cycle Industry G = Government

Item Number	Detailed Instructions- Form 540
	<p>I = Industrial M = Medical NP = Nuclear Power O = Other</p>
6	<p>Record the following: Carrier's Company Name Carrier's Company Address EPA ID No.: Record the carrier's EPA ID number if applicable, otherwise record N/A. Shipping Date: Record the date that the shipment is released to the carrier for transport. Contact / Telephone Number: The name and phone number of a responsible representative of the carrier's organization who can answer detailed questions concerning the shipment. Signature / Date: The signature of an authorized representative of the carrier acknowledging receipt of the waste for the shipment. Record the date that the carrier's signature is affixed.</p>
7	<p>Record the number of pages of each set of forms (i.e., number of 540/540A's, 541/541A's, and 542/542A's). Also, record the number of other pages of additional information. If there are no pages of a given form record "None".</p>
8	<p>Record a unique traceable number comprised of at least four number/letter characters assigned by the shipper. This number should be used on all continuation pages. The shipper may choose to use the same number recorded in Item 5 for "shipment number".</p>
9	<p>Record the following: Barnwell Waste Management Facility Operated by Chem-Nuclear Systems, LLC 740 Osborn Road, Barnwell, South Carolina 29812 Contact: Licensing Department Telephone Number: (803) 259-1781 Signature / Date: Leave blank for the consignee to complete.</p>
10	<p>The signature of the shipper or authorized representative.</p>
11	<p>Record the DOT's Basic Shipping Description (UN ID number, PSN, Hazard Class, and if applicable, packing group) for each package. Record any needed additional information as required by 49 Code of Federal Regulations. If the material is a reportable quantity - record RQ as appropriate. If the material is fissile excepted, record Fissile Excepted as appropriate. Following all DOT information, record a brief waste description. For Example: dry activated waste, dewatered resin, etc. This description should not conflict with any codes recorded on Form 541/541A, Item 11.</p>
12	<p>Record the type of radioactive label that appears on the package. White I Yellow II Yellow III "NA" If no label is required For other hazard class labels: Write out the Hazard Class Name, for example, Oxidizer.</p>

Item Number	Detailed Instructions- Form 540
	Note: Do not record Radioactive-LSA or Radioactive-SCO in this blank.
13	Record the package TI. If the TI is not required for the package, record "NA".
14	Record the physical form: "Solid", "Liquid", or "Gas" as appropriate Record the predominant chemical form: for example "oxides". Note: The Barnwell Waste Management Facility does not accept liquids for additional information; refer to the Barnwell Site Criteria Section 13.5.
15	List nuclides in the shipping package in accordance with 49 CFR. Separate multiple nuclides with a semicolon. DOT approved abbreviations are authorized.
16	Record the total package activity in appropriate SI units followed by appropriate conventional units. Use the SI unit Megabecquerel and the conventional unit Millicurie. For example, 10,000 mCi of activity would be recorded as: 370000 MBq; 10000 mCi (Scientific notation is authorized). Note: Conventional units must be in parenthesis.
17	For a shipment of LSA or SCO, record the correct group notation for example LSA-I, II, III or SCO-I,II). If the material is not LSA or SCO, record "NA".
18	Record the total package weight or volume with appropriate units. You may choose either of two options in completing this item: Use conventional units Use SI units followed by conventional units Example: 2.2 pounds of waste could either be recorded as 2.2 lb, or if using SI units it would be recorded as 1.0 kg; 2.2 lb.
19	Record the unique number for each package in the shipment assigned by the shipper. This number should be recorded on the manifest and also marked on the package exterior. Note: When shipping a licensed cask, record the Certificate of Compliance Number and the Model/Serial Number. For example: USA/9168/B(U) 8-120B-1
20	South Carolina Certification Statement: Record the date, signature of the shipper, or authorized representative, title and organization, and telephone number.
Consignee Use Only Section	If applicable, enter the Illinois Transaction Reference Number.

B) Form 541, Container and Waste Description:

The Form 541 is required for all shipments.

The purpose of this form is to record the waste data that is required by 10 CFR 20, 10 CFR 61, State Licenses, and the Barnwell Site Criteria (S20-AD-010).

When recording the weight of SNM nuclides the unit of grams (g) is used and it is not necessary to record the number in conventional units.

Exercise caution when choosing the codes found in the notes on the bottom of Form 541. Consult the Barnwell Site License and Barnwell Site Criteria for further guidance or contact the Barnwell Waste Management Facility Licensing Department.

Record the waste form total for Item 15 by recording the word "Total" in Item 15 (radionuclide column) and then recording the total quantity of MBq, mCi, SNM grams and Source Kilograms.

Record the package total for Item 15 by recording the words "Package Total" Item 15 (radionuclide column) and then recording the total quantity of MBq, mCi, SNM grams and Source Kilograms.

Record the shipment total for Items 7, 8, and 15 by recording the words "Shipment Total" as the last row entry in Item 5 on the last 541/541A and then recording the total quantities for Items 7, 8, and 15 in the associated columns.

Item Number	Detailed Instructions - Form 541
1	<p>Record the total number of Packages /Disposal Containers. This may be a different number than recorded on the Form 540, Item 3, when multiple disposal packages are contained within a single DOT package. For example, if multiple waste drums are shipped within an approved shipping cask (using the cask as the DOT package) the correct number for this item is the number of waste drums.</p> <p>Record the total net waste volume in cubic meters and cubic feet. For example, 7.5 ft³ of waste would be recorded as: 0.2124 m³ 7.5 ft³.</p> <p>Record the total net waste weight in kilograms and pounds. For example, 500 pounds of waste would be recorded as: 226.8 kg 500.0 lb.</p> <p>Special Nuclear Material Entries:</p> <p>Record the weight in grams for U-233, U-235, and Pu. Record the total number of packages in parenthesis () that contain each quantity of SNM in the same item with the SNM grams for that isotope. For example, a total of 1.0 gram of U-233 shipped in four different packages, would be recorded as: 1.0 g (4 pkg.). Include the unit "g" in the entry. The abbreviation pkg. may be used for package. NP may be used for Not Present.</p> <p>Record the grand total of SNM (U-233, U-235, and Pu). Include the unit "g" in the entry.</p>

Item Number	Detailed Instructions - Form 541
	<p>All Nuclides Entry: Record the total activity of all nuclides in Megabecquerels and in millicuries. For example: 50,000 Curies would be recorded as: 1.85E9 MBq; 5E⁷ mCi. Radionuclides below LLD should not be included.</p> <p>Tritium, C¹⁴, Tc⁹⁹, and I¹²⁹ Entries: Record the activity of Tritium, C¹⁴, Tc⁹⁹, and I¹²⁹ in Megabecquerels and in millicuries. For example: 5 millicuries of C14 would be recorded as: 185.0 MBq; 5.0 mCi. If the radionuclide is not present in the shipment record "NP" for not present. If the radionuclides are present in any of the containers within a shipment, but are identified in Item 15 in quantities below the Lower Limit of Detection (LLD), the quantities of these nuclides must be recorded as the sum of the respective LLD values. Place this summed value in parenthesis. For example: if one of the radionuclides was <LLD and had a summed LLD value of 1E⁻¹⁰ millicuries, this would be recorded as (3.7E⁻⁹ MBq; 1E⁻¹⁰ mCi). If both detectable and LLD based quantities of these radionuclides exist in containers making up the shipment, the sum of the detectable and "LLD-based" values must be reported separately, with the latter in parenthesis. For example, if C¹⁴ levels in some containers were <LLD and is summed up to be 1E⁻¹⁰ millicuries, while some other containers had detectable C¹⁴ at 0.5 millicuries, the entry would be: 18.5 MBq; 0.5 mCi (3.7E⁻⁹ MBq; 1E⁻¹⁰ mCi).</p> <p>Source Pound Entries: Record the total source weight in Kilograms (kg) and pounds (lb). For example, if 100 pounds of source material was being shipped this entry would be: 45.36 kg; 100.0 lb.</p>
2	Transfer the manifest number from Form 540, Item 8.
3	Record the total number of Form 541 or 541A pages.
4	Transfer the shipper's name and Shipment ID Number from Form 540, Item 5.
5	<p>Record a unique disposal container identification number. This entry is assigned by the shipper and may be alphanumeric. Record the unique State of South Carolina's Radioactive Waste Transport Permit number of the generator(s) contributing waste to a disposal container.</p> <p>Note: Each container number on a shipment must be unique.</p> <p>Only one generator may be listed per row. Items 5-10 & 16 data represents the total disposal container, while Items 11-15 are on a per generator and per waste form basis.</p> <p>Generators with multiple facility locations utilizing the same SC Transport Permit Number must indicate the facility address in this block.</p> <p>For process/collected waste, identify the state of origin for all waste.</p>

Item Number	Detailed Instructions - Form 541
6	<p>Using the codes found in Note 1 and Note 1A on the bottom of the Form 541, record the type of disposal container. Choose only one code from Note 1 and only one code from Note 1A. For example, a metal box would be assigned the code 2.</p> <p>If the container requires disposal in a structural overpack to provide structural stability, the suffix “-OP” should be recorded after the code.</p> <p>Note: The “-OP” designator should be used when the structural overpack is required for the package to achieve structural stability as defined in 10 CFR 61. The “-OP” designator is always required for stable waste in a HIC (Code 13). Thus the final code would be 13-A-OP.</p> <p>Information regarding acceptable stable waste forms/packages can be found in the Barnwell Site Criteria (S20-AD-010) or by contacting the Barnwell Waste Management Facility Licensing Department.</p> <p>When CNS Grapple Bail Liners are used, “GRAPPLE” is required to be identified.</p> <p>Liners containing non-CNS Grapple Bails must have appropriate lifting Cables attached in accordance with Step 11.5.</p> <p>When any poly or metal liner, pressure vessel, or high integrity container is used, identify the manufacturer, the model number, the manufacturer’s serial number, and the Certificate of Compliance number for the container, if applicable.</p> <p>When code 19 (other) is used, describe the container in Item 6. If necessary to adequately describe the container, the entry “see additional page” may be recorded in this item. The container should then be described on the additional page and that page count recorded on the Form 540, Item 7.</p>
7	<p>Record the waste container disposal volume using the SI unit cubic meter (m³) and the conventional unit cubic feet (ft³). For example, a 300 ft³ waste container would be recorded as: 8.495 m³; 300 ft³. Standard container volumes for common containers and directions for determining non-standard container dimensions are specified in the Barnwell Site Criteria. (S20-AD-010)</p> <p>Note: For processed and collected waste, the value recorded in Item 12 must include an allocation for the packages volume. The sum of the individual generator volumes (Item 12) must equal the package volume (Item 7).</p> <p>Record the shipment total for Items 7, 8, and 15 by recording the words “Shipment Total” as the last row entry in Item 5 on the last 541/541A and then recording the total quantities for Items 7, 8, and 15 in the associated columns.</p>
8	<p>List the weight of the waste plus disposal container in the SI unit kilograms (kg) and the conventional unit pounds (lb). For example, a 5,000 lb package would be recorded as: 2270 kg; 5000 lb.</p> <p>Record the shipment total for Items 7, 8, and 15 by recording the words “Shipment Total” as the last row entry in Item 5 on the last 541/541A and then recording the total quantities for Items 7, 8, and 15 in the associated columns.</p>
9	<p>Record the highest radiation level on contact with the disposal container in SI units of millisieverts (mSv/hr) and conventional units of millirem (mrem/hr). For example, a package that has a maximum radiation reading of 195 mrem/hr would be recorded as: 1.95 mSv/hr; 195 mrem/hr.</p>

Item Number	Detailed Instructions - Form 541
10	<p>Record the highest contamination levels anticipated on the exterior of the disposal container in the SI unit of Megabecquerel per 100 square centimeters (MBq/100 cm²) and the conventional units of disintegration per minute per 100 square centimeters (dpm/100 cm²). For example: Contamination levels of 100 dpm/100 cm² would be recorded as 1.67E-6 MBq/100 cm²; 100 dpm/100 cm². Do not use BKG for background unless the level is recorded also.</p>
11	<p>Using the codes found in Note 2 and Note 2A at the bottom of the Form 541, record the codes that most specifically describe the type of waste in the container. Choose up to three Note 2 codes, which predominate by volume. Choose all Note 2A codes that are applicable. For example, a dewatered mixed-resin waste might be assigned the codes 32, G, H, and I depending on the unique characteristics of the waste.</p> <p>For different waste forms contained in the same disposal container, the codes should be associated with the rest of the description required in items 12-15 for each listed waste form. Discrete waste forms, in significant quantities, must be individually identified and described in Items 11-15.</p> <p>Discrete waste forms that must be described individually are: Resin (Code 30, 31, 32); Dry Active Waste (Codes 35, 39, 40); Filter Media used in liquids (this does not include resins or aqueous filters): (Codes 26, 20); Cartridge/Mechanical Filters -Aqueous (Code 27); Solidified Liquids (Code 25 and Code 90 in Item 13; Code 38 and Code 90 in Item 13); Equipment/Components (Code 33, 43); Bulk Waste (Code 11 in Item 6); Biological Materials (Codes 41, 42); Ash (Code 21); Air Filtration Filters (Code K); Asbestos (Code L); Combustibles (Code I); Non-combustibles (Code J, 22, 29); Sources (Code 36).</p> <p>If code 59 (other) is used, a written explanation is required. This additional explanation may be recorded in item 11 or the entry "see additional page" may be recorded and an additional page attached. The additional page must be included in the Form 540 Item 7 page counts.</p>
12	<p>Record the volume in the SI unit of cubic meters and the conventional unit of cubic feet of the waste per generator and per waste form not to exceed three digits past the decimal. (Example 0.001)</p>
13	<p>Using the codes found in Note 3 and Note 3A on the bottom of Form 541, record the codes that apply. In addition, the media vendor and brand name must be recorded in this column as well.</p> <p>If the media is intended to provide stability for the waste in accordance with 10CFR61, State, and Site requirements, the entry "-S" must be recorded following the appropriate code.</p> <p>For all solidification or stabilization media, also record the vendor (manufacturer) and brand name.</p> <p>If code 99 (other) is used a written explanation is required. This additional explanation may be recorded in Item 13 or the entry "see additional page" may be recorded and an additional page attached. The additional page must be included in the Form 540 Item 7 page counts.</p>

Item Number	Detailed Instructions - Form 541
14	<p>List the most prevalent chemical form of the waste.</p> <p>Information in Item 14 should expand upon the entry on the Form 540, Item 14. Record significant chemicals like lime if used.</p> <p>Record the name of chelating agents that are present in amounts greater than 0.1% by weight of the waste. In the associated column, record the weight % of the chelating agent if >0.1%. If no chelating agents are present record "NP" for not present in both sub columns of Item 14. If large processes using chelating agents were used record the process name. Use additional sheets as needed. Record additional page counts on the Form 540, Item 7.</p>
15	<p>List all significant radionuclides (approved abbreviations are authorized) and the nuclide's activity in Megabecquerels followed by the Millicurie value. For example: 1.0 mCi (millicuries) of Cs¹³⁷ would be recorded as follows: Cs¹³⁷ 37 MBq; 1.0 mCi.</p> <p>If the waste in the container is from multiple generators or is of multiple waste forms, the radionuclides must be broken down to the corresponding generator and waste form with totals for each waste stream, and for each generator specifically.</p> <p>When the radionuclides tritium (H-3), C-14, Tc-99, or I-129 are present, but the quantities are below the LLD, note the radionuclide and report the LLD value in parentheses (). After listing the individual radionuclides as described above, enter the word "Total" on a new line and enter the total activity contained in the container.</p> <p>However, if any LLD values were included in the container, these values should not be included in the container sum because they will be totaled separately under Item 1.</p> <p>After listing all the package's radionuclides as described above, record the word "Total" on a new line and record the total activity in the package.</p> <p>Note: The activity for uranium and thorium in source material and U-233, U-235, and plutonium in special nuclear material must be reported in megabecquerels. The quantity of these isotopes must be reported, in kilograms for source material -- including the abbreviation "kg", and in grams for special nuclear material -- including the abbreviation "g". The weight quantities must be reported in brackets [], either adjacent to the activity listing or below the radionuclide listing.</p> <p>Record the shipment total for Items 7, 8, and 15 by recording the words "Shipment Total" as the last row entry in Item 5 on the last 541/541A and then recording the total quantities for Items 7, 8, and 15 in the associated columns.</p>
16	<p>Record the waste classification and the stability of the waste using the appropriate code provided in Item 16 for the most restrictive waste stream.</p>

C) Form 542 - Manifest Index and Regional Compact Tabulation

Form 542 is required for all waste shipments that are processed or collected.

Note: Any shipment that requires a Form 542 must comply with Section 21.

Item Number	Detailed Instructions - Form 542
1	Record the collector or processor's name. Record the collector or processor's SC Radioactive Waste Transport Permit Number. Record the shipping date.
2	Transfer the manifest number from the Form 540, Item 8.
3	Record the total number of 542 and 542A pages.
4	<p>In each row, record one generator's South Carolina Waste Transport Permit Number and one waste form.</p> <p>Use as many rows as is needed to uniquely record each waste form that the generator is shipping. For each waste form entry, record all entries as required in Form 542 columns 5-11F.</p> <p>Discrete waste forms that must be described individually are: Resin (Code 30, 31, 32); Dry Active Waste (Codes 35, 39, 40); Filter Media used in liquids (this does not include resins or aqueous filters): (Codes 26, 20); Cartridge/Mechanical Filters-Aqueous (Code 27); Solidified Liquids (Code 25 and Code 90 in Item 13; Code 38 and Code 90 in Item 13); Equipment/Components (Code 33, 43); Bulk Waste (Code 11 in Item 6); Biological Materials (Codes 41, 42); Ash (Code 21); Air Filtration Filters (Code K); Asbestos (Code L); Combustibles (Code I); Non-combustibles (Code J, 22, 29); Sources (Code 36).</p> <p>Ensure that all generators whose waste is being shipped are represented.</p>
5	Record the generator name and telephone number.
6	Record the complete address of the generator's facility.
6A	Record the waste form nomenclature. For example; dewatered resin encapsulated, sources (unless placed in a HIC), dry activated waste, etc.
7	Record the approximate volume in cubic meters followed by the cubic feet (not including the container) of the preprocessed waste. For example, a waste that was 96 ft ³ prior to processing would be recorded as: 2.72 m ³ ; 96 ft ³ .
8	<p>List the previous manifest number(s) applicable to the waste that has been attributed to the generator listed in Item 5.</p> <p>Record the date(s) of waste receipt by the shipper identified on Form 540, item 5.</p>
9	Record the proper waste code, "P" or "C" using the definitions of waste processor and waste collector in Appendix G of 10 CFR Part 20. Do not mix processed and collected waste on the same line - list separately.
10	Identify the originating State of the original generator of the waste. Standard state abbreviations may be used.

Item Number	Detailed Instructions - Form 542
11	<p>For each original generator and waste form listed in Item 5, list the total source material in kilograms and in pounds.</p> <p>For each original generator and waste form listed in Item 5, list the total special nuclear material in grams.</p> <p>For each original generator and waste form listed in Item 5, list the total activity attributed to the generator in Megabecquerels and in Millicuries.</p> <p>For each original generator and waste form listed in Item 5, list the volume attributed to the generator in cubic meters and in cubic feet.</p> <p>For each original generator and waste form listed in Item 5, list the weight attributed to the generator in pounds. (SI units are not required for this entry.)</p> <p>For each original generator and waste form listed in Item 5, list the maximum on-contact radiation level for the package that this waste is packaged in. Record in units of millirem per hour. (SI units are not required for this entry.)</p> <p>Record the totals for columns 11A-11E for each generator by drawing a horizontal line below the last entry for the generator and entering the generator column totals.</p> <p>Record the overall column totals at the bottom of the Form 542.</p>

Attachment 24.4

**Documentation Required for Class C Waste Shipment
Acceptance at the Barnwell Site**

These instructions outline documentation required for Class C waste shipment acceptance. This documentation is required in addition to other applicable requirements of S.C. License 097, Barnwell Site Criteria and State and Federal regulations. Waste classification must be performed in accordance with SC License 097 (Reference 2.1). This additional information will be used to evaluate the shipment for acceptance. In order to have consistency, the information provided on the attached form, or equivalent, shall be completed and sent with each shipment.

Waste, other than irradiated hardware or sources, shall be classified in accordance with Section 15. A more detailed explanation is provided in the NRC Low Level Waste Licensing Branch Technical Position on Radioactive Waste Classification (Reference 2.6).

For irradiated hardware, classification must be performed in accordance with Section 16.

For Sources, classification must be performed in accordance with Section 13.4.

1. Waste Description

The item, component, or medium in which the radioactivity is present and the physical nature of the waste should be described. Example: 5 control rod blades, 25 dewatered filters, etc.

2. Container Volume/Weight

The disposal volume (ft³) is used to determine allocations, waste densities, and disposal fees. The volume and weight of waste materials only shall be used in determining radionuclide concentrations.

3. Container Type

The disposal container should be clearly identified in terms of its size, composition and construction.

4. Radiation Levels

The maximum disposal container dose rate (1) on contact and (2) in air at one foot shall be clearly stated.

5. Total Curie Content

Self-explanatory

6. Radionuclide Concentrations

A detailed list of the concentrations of contained radionuclides in microcuries per cubic centimeter and concentrations of each transuranic radionuclide in nanocuries per gram shall be provided. The total activity of each radionuclide in the waste material shall also be given.

7. Waste Classification Method

The methods used to calculate radionuclide concentrations in Class C waste shall be specified. Indicate if the waste was classified using the BTP, Barnwell Rule of 10, etc.

Attachment 24.5

CLASS "C" WASTE CLASSIFICATION RECORD (EXAMPLE)

Generator Name

Shipment ID Number

1. Waste Description: _____

2. Volumes/Weight:

(a) Container Volume (Ft³): _____

(b) Waste Volume (cm³): _____

(c) Waste Weight (lb): _____

3. Container Type: _____

4. Radiation Levels:

(a) Maximum Dose Rate of Disposal Container on contact: _____

(b) At One (1) Foot: _____

5. Total curie content: _____

6. Radionuclide concentrations:

Radionuclides	Each Radionuclide Concentration (Microcuries/cc)	Total Activity of Each Radionuclide	Each Transuranic Concentration (Nanocuries/gm)
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____
_____	_____	_____	_____

Total Concentration of all Transuranics: _____

(Attachment 24.5 - Continued)

CLASS "C" WASTE CLASSIFICATION RECORD (EXAMPLE)

Generator Name

Shipment ID Number

7. Waste Classification Methods:

(a) Describe method: _____

SIGNATURE: _____ DATE: _____

TITLE: _____

COMPANY: _____

Barnwell Uniform Low-Level Radioactive Waste Manifest Forms - Example

FORM 540 (6-97)

Attachment 24.6 (continued)

Barnwell Uniform Low-Level Radioactive Waste Manifest Forms - Example

[illegible]

Attachment 24.6 (continued)

Barnwell Uniform Low-Level Radioactive Waste Manifest Forms – Example

FORM 542			BARNWELL WASTE MANAGEMENT FACILITY			1. WASTE COLLECTOR/PROCESSOR				2. MANIFEST NUMBER						
UNIFORM LOW-LEVEL RADIOACTIVE WASTE MANIFEST MANIFEST INDEX AND REGIONAL COMPACT TABULATION List all original "PROCESSED Waste" generators (if any) before "COLLECTED WASTE" generators.						NAME		SHIPPER USE ONLY		3. PAGE <u>1</u> OF _____ PAGE(S)						
						S.C. RADIOACTIVE WASTE TRANSPORT PERMIT NUMBER										
						SHIPPING DATE										
4.	5.	6.	6A.	7.	8.	9.	10.	11. AS PROCESSED/COLLECTED TOTAL								
SC TRANSPORT PERMIT NUMBER	GENERATOR NAME AND TELEPHONE NUMBER	GENERATOR FACILITY ADDRESS	WASTE DESCRIPTION (NOMENCLATURE)	PREPROCESSED WASTE (OR MATERIAL) VOLUME (m ³) (ft ³)	MANIFEST NUMBER (S) UNDER WHICH WASTE (OR MATERIAL) RECEIVED AND DATE OF RECEIPT	WASTE CODE P=PROCESSED C=COLLECTED	ORIGINATING COMPACT REGION OR STATE	A. SOURCE MATERIAL (kg) (lb)		B. SNM (g)	C. ACTIVITY (MBq) (mCi)		D. VOLUME (m ³) (ft ³)		E. WEIGHT (lb)	F. MAXIMUM PACKAGE RADIATION LEVEL (mrem/hr)
TOTALS OF ALL PAGES (542 AND 542A)																

Attachment 24.7

Displacement of Steel Drums and Standard B-25 Boxes – Drum Volumes

4-GALLON DRUM_____	0.55 CUBIC FEET
5-GALLON DRUM_____	0.68 CUBIC FEET
16-GALLON DRUM_____	2.00 CUBIC FEET
30-GALLON DRUM_____	4.10 CUBIC FEET
52-GALLON DRUM_____	7.10 CUBIC FEET
55-GALLON DRUM_____	7.50 CUBIC FEET
60-GALLON DRUM_____	8.20 CUBIC FEET
70-GALLON DRUM_____	9.60 CUBIC FEET
79-GALLON DRUM_____	10.80 CUBIC FEET
83-GALLON DRUM_____	11.30 CUBIC FEET
85-GALLON DRUM_____	11.60 CUBIC FEET
89-GALLON DRUM_____	12.10 CUBIC FEET
96-GALLON DRUM_____	13.10 CUBIC FEET
110-GALLON DRUM_____	15.00 CUBIC FEET

Note: To obtain a volume for a drum other than listed above, contact the Barnwell Licensing Department.

BOX VOLUMES

* STANDARD B-25 BOX _____ 95 CUBIC FEET

* Volumes for other B-25 type boxes (i.e.: type A, drum overpacks, etc.) are to be obtained through the use of Section 7, Volume and Weight Measurement Criteria.

Attachment 24.8

Example Request Approval for Sealed Source/Special Form Radioactive Material

Date:

Licensing Manager
Chem-Nuclear Systems
740 Osborn Road
Barnwell, SC 29812

Dear Sir:

Customer Name requests approval for the source(s) described below. These items will be placed in a DOT certified shipping container and surrounded on all sides with cement encapsulation media, with a minimum compressive strength of at least 2500 psi. The minimum encapsulation will be four inches.

Waste Form and General Description:

Isotope (Per Source):

Activity (Per Source):

Generator (Atlantic Compact Generators Only) and Address:

If you have any additional questions, please feel free to contact me.

Sincerely,

Signature of Customer

Attachment 24.9

Lead Shielding Request - Example

Lead used for radiation shielding purposes may be acceptable for disposal at the Barnwell Disposal Facility. Requests for acceptance of non-radioactively contaminated lead, specifically used for shielding purposes, must be evaluated by CNS to ensure regulatory compliance. In order for Chem-Nuclear to evaluate your request, please provide the following information prior to making waste shipments containing lead shielding.

1. Type of lead used (sheet, shot, etc.)
2. Amount of lead used (pounds/thickness): please provide a detailed sketch of the waste packaging specifically showing the location and thickness of the lead.
3. Container type and size (can be shown in sketch)
4. Location of lead in container, i.e.: top, bottom, sides (can be shown in sketch)
5. Description of waste requiring shielding (waste form, total activity, isotopic distribution, and total volume)
6. Waste classification (A, B, or C)
7. Approximate radiation dose rate prior to shielding
8. Appropriate radiation dose after shielding

Attachment 24.10

Typical Waste Package Data Summary - Example

Shipment Identification Number: _____

Package Identification Number: _____

Generator Name/ SC Transport Permit #	Activity (mCi)	Waste Volume (cu.ft.)	Waste Weight (lbs)	Waste Volume Plus Allocated Container Volume (cu.ft.)	Waste Weight Plus Allocated Container Weight (lbs)
Gen #1		L	R	$L + Q(L/P)$	$R + W(R/V)$
Gen #2		M	S	$M + Q(M/P)$	$S + W(S/V)$
Gen #3		N	T	$N + Q(N/P)$	$T + W(T/V)$
Gen #4		O	U	$O + Q(O/P)$	$U + W(U/V)$
Waste Total		P	V	Total Vol (sum of 4 cells above)	Total Weight (sum of 4 cells above)
Disposal Volume of Container (external volume less waste volume)		Q			
Weight of Container (without waste)			W		
TOTAL		P + Q	V + W		

Note: In this example, letter designations are used in some cells and formulas shown in other cells for example purposes.

Attachment 24.11

Irradiated Hardware Liner Inventory Log - Example

A. RESPONSIBLE PERSONNEL: All persons entering data on this sheet must complete the following table.				
Printed Name	Initials	Signature	Title	Organization

LINER # _____ LINER SER. # _____ Page _____ of _____

The following processed irradiated hardware has been loaded into this liner. Annotate any unused blocks below as N/A.

B. COMPONENT INVENTORY:				
	Item Description	ID #	Processor Confirm	Plant Representative Verify
1.				
2.				
3.				
4.				
5.				
6.				
7.				
8.				
9.				
10.				
11.				
12.				
13.				
14.				
15.				

C. MISCELLANEOUS COMPONENTS:				
	Item Description	ID #	Processor Confirm	Plant Representative Verify
1.				
2.				
3.				
4.				
5.				

D. CERTIFICATION:
Certification is hereby made that this liner has been classified with a classification/characterization program accepted by Chem-Nuclear Barnwell Licensing, has been processed in accordance with procedures approved by the waste generator, contains only the inventory of items listed above, and does not include any spent fuel or fuel bearing components. Furthermore, the shipper certifies that all spent fuel has been physically accounted for at their facility.

Cognizant Waste Generator Representative _____ Title _____ Date _____